

Accepted Manuscript

A new model for rolling element bearing defect size estimation

Aoyu Chen, Thomas R. Kurfess

PII: S0263-2241(17)30584-5

DOI: <http://dx.doi.org/10.1016/j.measurement.2017.09.018>

Reference: MEASUR 4968

To appear in: *Measurement*

Received Date: 16 May 2017

Revised Date: 18 July 2017

Accepted Date: 11 September 2017



Please cite this article as: A. Chen, T.R. Kurfess, A new model for rolling element bearing defect size estimation, *Measurement* (2017), doi: <http://dx.doi.org/10.1016/j.measurement.2017.09.018>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

- [3] T.R. Kurfess, S. Billington, S.Y. Liang, Advanced diagnostic and prognostic techniques for rolling element bearings, *Condition Monitoring and Control for Intelligent Manufacturing*, Springer, 2006, pp. 137-165.
- [4] N. Tandon, A comparison of some vibration parameters for the condition monitoring of rolling element bearings, *Measurement*, 12 (1994) 285-289.
- [5] N. Sawalhi, R. Randall, Vibration response of spalled rolling element bearings: Observations, simulations and signal processing techniques to track the spall size, *Mechanical Systems and Signal Processing*, 25 (2011) 846-870.
- [6] L. Niu, H. Cao, Z. He, Y. Li, Dynamic modeling and vibration response simulation for high speed rolling ball bearings with localized surface defects in raceways, *Journal of Manufacturing Science and Engineering*, 136 (2014) 041015.
- [7] M. Behzad, A.R. Bastami, D. Mba, A new model for estimating vibrations generated in the defective rolling element bearings, *Journal of Vibration and Acoustics*, 133 (2011) 041011.
- [8] S. Khanam, N. Tandon, J. Dutt, Fault size estimation in the outer race of ball bearing using discrete wavelet transform of the vibration signal, *Procedia Technology*, 14 (2014) 12-19.
- [9] A.M. Ahmadi, C.Q. Howard, D. Petersen, The path of rolling elements in defective bearings: Observations, analysis and methods to estimate spall size, *Journal of Sound and Vibration*, 366 (2016) 277-292.
- [10] A. Moazenahmadi, D. Petersen, C. Howard, N. Sawalhi, Defect size estimation and analysis of the path of rolling elements in defective bearings with respect to the operational speed, *INTER-NOISE and NOISE-CON Congress and Conference Proceedings*, Institute of Noise Control Engineering, 2014, pp. 4242-4251.
- [11] W.A. Smith, C. Hu, R.B. Randall, Z. Peng, Vibration-Based Spall Size Tracking in Rolling Element Bearings, *Proceedings of the 9th IFToMM International Conference on Rotor Dynamics*, Springer, 2015, pp. 587-597.
- [12] A. Moazen-Ahmadi, C.Q. Howard, A defect size estimation method based on operational speed and path of rolling elements in defective bearings, *Journal of Sound and Vibration*, 385 (2016) 138-148.
- [13] A.M. Ahmadi, D. Petersen, C. Howard, A nonlinear dynamic vibration model of defective bearings—The importance of modelling the finite size of rolling elements, *Mechanical Systems and Signal Processing*, 52 (2015) 309-326.
- [14] J.-Y. Shen, C.-W. Tseng, I. Shen, Vibration of rotating disk/spindle systems with flexible housing/stator assemblies, *Journal of Sound and Vibration*, 271 (2004) 725-756.
- [15] R.B. Randall, J. Antoni, Rolling element bearing diagnostics—a tutorial, *Mechanical Systems and Signal Processing*, 25 (2011) 485-520.
- [16] A. Chen, *MACHINE TOOL SPINDLE BEARING DIAGNOSTICS UNDER OPERATING CONDITIONS*, Georgia Institute of Technology, 2017.

Highlights:

- Entry signal is used to find the moment when the ball center arrives entry edge.
- All the parameters for the estimation can be obtained from the vibration signal.
- Experiments were performed on a CNC machine tool rather than test rigs.