Accepted Manuscript

Margins Associated with Loss of Assured Safety for Systems with Multiple Weak Links and Strong Links

Jon C. Helton, Dusty M. Brooks, Cédric J. Sallaberry

 PII:
 S0951-8320(18)30384-3

 DOI:
 https://doi.org/10.1016/j.ress.2019.106548

 Article Number:
 106548

 Reference:
 RESS 106548



To appear in: Reliability Engineering and System Safety

Received date:4 April 2018Revised date:7 June 2019Accepted date:26 June 2019

Please cite this article as: Jon C. Helton, Dusty M. Brooks, Cédric J. Sallaberry, Margins Associated with Loss of Assured Safety for Systems with Multiple Weak Links and Strong Links, *Reliability Engineering and System Safety* (2019), doi: https://doi.org/10.1016/j.ress.2019.106548

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

HIGHLIGHTS

- Representations for margins associated with loss of assured safety (LOAS) for weak link (WL)/strong link (SL) systems,
- CDFs for failure time margins defined by (time at which SL system fails) (time at which WL system fails),
- CDFs for SL system property values at LOAS,
- CDFs for WL/SL property value margins defined by (property value at which SL system fails) (property value at which WL system fails),
- CDFs for SL property value margins defined by (property value of failing SL at time of SL system failure) (property value of this SL at time of WL system failure),
- Demonstration of a sampling-based verification strategy

Chillip Martin

Margins Associated with Loss of Assured Safety for Systems with Multiple Weak Links and Strong Links

Jon C. Helton^{1*}, Dusty M. Brooks², Cédric J. Sallaberry³

¹Dept. of Mathematics and Statistics, Arizona State University, Tempe, AZ 85287-1804, USA ²Structural and Thermal Analysis Dept., Sandia National Laboratories, Albuquerque, NM 87185-0748, USA ³Engineering Mechanics Corporation of Columbus, Columbus, OH 43221-1735, USA

Abstract

Representations for margins associated with loss of assured safety (LOAS) for weak link (WL)/strong link (SL) systems involving multiple time-dependent failure modes are developed. The following topics are described: (i) defining properties for WLs and SLs, (ii) background on cumulative distribution functions (CDFs) for link failure time, link property value at link failure, and time at which LOAS occurs, (iii) CDFs for failure time margins defined by (time at which SL system fails) – (time at which WL system fails), (iv) CDFs for SL system property values at LOAS, (v) CDFs for WL/SL property value margins defined by (property value at which SL system fails) – (property value at which WL system fails), and (vi) CDFs for SL property value margins defined by (property value at which WL system fails), and (vi) CDFs for SL property value of this SL at time of WL system failure). Included in this presentation is a demonstration of a verification strategy based on defining and approximating the indicated margin results with (i) procedures based on algorithms for sampling-based approximations.

Keywords: Aleatory uncertainty, Margins, Loss of assured safety, Strong link, Verification, Weak link

1. Introduction

Representations for margins associated with loss of assured safety (LOAS) for weak link (WL)/strong link (SL) systems [1-6] involving multiple time-dependent failure modes are developed. As described in Ref. [7], the descriptor "loss of assured safety" for the performance under accident conditions (e.g., a fire) of a high consequence system with multiple WLs and SLs is used for the situation in which (i) a necessary set of SL failures places the system in a potentially operational condition before (ii) an appropriate set of WL failures places the system in an inoperable state. In contrast, safety is "assured" if (i) an appropriate set of SL failures places the system in a potentially operational condition. Consistent with the preceding description, LOAS does not mean that the accident will progress to operation of the high consequence system; rather, it only signifies that certain conditions exist that could contribute to this progression.

^{*}Corresponding author: Department 1514, Sandia National Laboratories, Albuquerque, NM 87185-0748 USA. E-mail: jchelto@sandia.gov.

With respect to terminology, a WL is a component of a high consequence system that is intended to fail under accident conditions and thereby contribute to rendering the system inoperable. In contrast, a SL is a component that is essential to the intended operation of a high consequence system whose failure under accident conditions contributes to placing the system in a state for which unintended operation of the system could potentially occur but is not certain to occur. In the design of a high consequence system, (i) a specific WL may have the sole purpose of deactivating the system under accident conditions or (ii) it may have a function that is essential to the operation of the system and also have deliberately incorporated design properties that make it more likely to fail under accident conditions than a SL. For both WLs and SLs, failure corresponds to some form of mechanical or electrical failure. However, for WLs, "failure" is actually a "success" as this failure contributes to deactivating the system and thus preventing an unintended operation of the system. The designations WL and SL are used because individual WLs in a high consequence system are designed to be more susceptible to failure under accident conditions than individual SLs.

In general, a high consequence system will have nWL > 1 WLs and nSL > 1 SLs. In the following, (i) the *nWL* WLs associated with a high consequence system will be referred to as a WL system, (ii) the *nSL* SLs associated with a high consequence system will be referred to as a SL system, and (iii) the *nWL* WLs and *nSL* SLs associated with a high consequence system will be referred to as a WL/SL system.

Margins defined by the following differences are considered in this presentation:

(i) (time at which SL system fails) – (time at which WL system fails),

(ii) (property value at which SL system fails) – (property value at which WL system fails),

and

(iii) (property value of failing SL at time of SL system failure) – (property value of this SL at time of WL system failure).

The development of the indicated margins in this presentation builds on previous work in Refs. [7; 8]. Specifically, Ref. [7] develops representations for the probability of loss of assured safety (PLOAS) for WL/ SL systems involving multiple time-dependent failure modes, and Ref. [8] develops representations for property values associated with the failure of individual links in a system with multiple WLs and SLs.

The following topics are described in this presentation: (i) defining properties for WLs and SLs (Sect. 2), (ii) background on cumulative distribution functions (CDFs) for link failure time, link property value at link failure, and time at which LOAS occurs (Sect. 3), (iii) CDFs for failure time margins (Sect. 4), (iv) CDFs for system property values at LOAS (Sect. 5), (v) CDFs for margins based on WL and SL property values (Sect. 6), and (vi) CDFs for margins involving only SL property values (Sect. 7). The presentation then ends with a summary discussion (Sect. 8).

Verification is an important component of any analysis used to support important decisions [9-13], where verification corresponds to "the process of determining that a model implementation accurately represents the developers conceptual description of the model and the solution to the model" ([9], p. 3). An important part of this presentation is the demonstration of a verification strategy based on defining and approximating the margin results of interest with (i) procedures based on formal integral representations and associated quadrature approximations and (ii) procedures based on algorithms for sampling-based approximations. The two procedures have very different mathematical structures and are implemented independently of each other. As a result, agreement between margin results obtained with the two procedures provides a strong verification result that the procedures have both (i) correct mathematical derivations and (ii) correct numerical implementations. Fortunately, the indicated agreement was observed and is extensively illustrated.

The presented work has been performed in support of the National Nuclear Security Administration's (NNSA's) mandate for the quantification of margins and uncertainties (QMU) in analyses of the United States' nuclear stockpile (see Refs. [14-17] for summary discussions of NNSA's mandate for QMU, Refs. [18-28] for additional background on the development of NNSA's mandate for QMU, and Refs. [29-40] for recent work on the implementation of NNSA's mandate for QMU).

The content of this paper is based on a previously published Sandia National Laboratories technical report [41].

2. WL/SL Properties

The failure time CDF for a single WL or SL is based on the following assumed properties of that link for the time interval $t_{mn} \le t \le t_{mx}$, where t_{mn} and t_{mx} define the endpoints of the time interval considered for analysis:

$$\overline{p}(t) =$$
 increasing positive function defining nominal link property for $t_{mn} \le t \le t_{mx}$, (2.1)

- $\overline{q}(t) = \text{ decreasing or constant-valued positive function defining nominal failure value}$ for link property for $t_{mn} \le t \le t_{mx}$, (2.2)
- $d_A(\alpha)$ = density function for a positive variable α used to characterize aleatory uncertainty in link property, (2.3)
- $d_B(\beta) =$ density function for a positive variable β used to characterize aleatory uncertainty in link failure value, (2.4)

$$p(t \mid \alpha) = \alpha \overline{p}(t) = \text{ link property value for } t_{mn} \le t \le t_{mx} \text{ given } \alpha,$$
 (2.5)

and

$$q(t \mid \beta) = \beta \overline{q}(t) = \text{ link failure value for } t_{mn} \le t \le t_{mx} \text{ given } \beta.$$
(2.6)

Further, $d_A(\alpha)$ and $d_B(\beta)$ are assumed (i) to be defined on intervals $[\alpha_{mn}, \alpha_{mx}]$ and $[\beta_{mn}, \beta_{mx}]$ and (ii) to equal zero outside these intervals. Although this does not have to be the case, it is anticipated that α and β will be assigned distributions with a mode of 1.0 in most analyses so that $\overline{p}(t)$ and $\overline{q}(t)$ will be the modes (i.e., most likely values) for $p(t|\alpha)$ and $q(t|\beta)$. For given values of α and β , link failure occurs at the time t at which $\alpha \overline{p}(t) = \beta \overline{q}(t)$.

As indicated in Eqs. (2.3) and (2.4), the variables α and β are used for the incorporation of the effects of aleatory uncertainty into the analysis of a WL/SL system. Specifically, aleatory uncertainty is used as a descriptor for random variability in the properties of a system and is distinct from epistemic uncertainty, which results from a lack of knowledge about the value of a quantity that has a fixed (i.e., unique) but poorly known value. Additional discussion of the role of aleatory uncertainty and epistemic uncertainty in the analysis of complex systems is available in Refs. [16; 31; 42-52].

This presentation uses a notional WL/SL system with nWL = 2 WLs and nSL = 2 SLs to illustrate margin calculations. Property definitions for the four links are summarized in Table 1 and illustrated in Fig. 1. However, the derived results are more general as they are valid for $nWL \ge 2$ and $nSL \ge 2$.

Table 1 Defining properties for two WLs and two SLs used in the illustration of the definition and calculation of margins for WL/SL systems.

Fig. 1 Summary plots of the properties of two WLs and two SLs used in the illustration of the definition and calculation of margins for WL/SL systems with the dashed lines corresponding to the boundaries defined by $[\alpha_{mn}\bar{p}(t), \alpha_{mx}\bar{p}(t)]$ and $[\beta_{mn}\bar{q}(t), \beta_{mx}\bar{q}(t)]$: (a) WL 1, (b) WL 2, (c) SL 1, and (d) SL2.

The defining values used in this presentation for the quantities introduced in Eqs. (2.1)-(2.6) are notional and intended for the illustration of concepts and computational procedures. The values used in an analysis for a real system would be based on results obtained from both mechanistic modeling and physical testing. Further, the final assembly, assessment and summarization of the information obtained from multiple sources would most likely be performed through an expert review process [53-60].

3. Background: CDFs for Link Failure Time, Link Property Value at Link Failure, and Time at which LOAS Occurs

The CDF for link failure time is defined by

$$CDF_{T}(t) = \int_{\alpha_{mn}}^{\alpha_{mx}} \left[\int_{\beta_{mn}}^{F(\alpha,t)} d_{B}(\beta) d\beta \right] d_{A}(\alpha) d\alpha$$

$$= \int_{\alpha_{mn}}^{\alpha_{mx}} CDF_{B}[F(\alpha,t)] dCDF_{A}(\alpha),$$
(3.1)

and extensively discussed in Ref. [7], where (i) the first integral is a Riemann integral with

$$F(\alpha,t) = \alpha \overline{p}(t) / \overline{q}(t) = \alpha / r(t) \text{ and } r(t) = \overline{q}(t) / \overline{p}(t)$$
(3.2)

and (ii) the second integral is a Riemann-Stieltjes integral with

$$CDF_A(\alpha) = \int_{\alpha_{mn}}^{\alpha} d_A(\tilde{\alpha}) d\tilde{\alpha} \text{ and } CDF_B(\beta) = \int_{\beta_{mn}}^{\beta} d_B(\tilde{\beta}) d\tilde{\beta}.$$
 (3.3)

The CDFs for link failure time for the four links defined in Table 1 and illustrated in Fig. 1 are shown in Fig. 2a. Quadrature and sampling-based procedures for the estimation of CDFs for link failure time are discussed and illustrated in Ref. [7].

Fig. 2 Illustration of failure properties for links defined in Table 1: (a) CDFs for link failure time (i.e., $CDF_{T,WL1}(t)$, $CDF_{T,WL2}(t)$, $CDF_{T,SL1}(t)$ and $CDF_{T,SL2}(t)$), and (b) CDFs for link property at time of link failure (i.e., $CDF_{P,WL1}(p | [t_{mn}, t_{mx}])$, $CDF_{P,WL2}(p | [t_{mn}, t_{mx}])$, $CDF_{P,SL1}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,SL2}(p | [t_{mn}, t_{mx}])$ with $[t_{mn}, t_{mx}] = [0, 200]$.

The CDF for link property at time of link failure is formally defined in Eq. (8.1) of Ref. [8] by

$$CDF_{p}(p | [t_{mn}, t_{mx}]) = \text{probability that link fails at a value less than or equal to } p$$

in the time interval $[t_{mn}, t_{mx}]$
$$= \int_{t_{mn}}^{t_{mx}} CDF_{p}(p | \tau) dCDF_{T}(\tau)$$
$$= \int_{t_{mn}}^{t_{mx}} CDF_{p}(p | \tau) d_{T}(\tau) d\tau,$$
(3.4)

where (i) $CDF_{p}(p|\tau)$ is the CDF for link property value p at link failure conditional on link failure occurring at time τ , and (ii) $d_{T}(\tau)$ is the density function for link failure time defined by

$$d_{T}(\tau) = dCDF_{T}(\tau) / d\tau$$

$$= \left[d\left[\overline{q}(\tau) / \overline{p}(\tau)\right] / d\tau \right] \int_{\alpha_{mn}}^{\alpha_{mx}} d_{B} \left[\alpha / r(\tau) \right] \alpha d_{A}(\alpha) d\alpha \qquad (3.5)$$

$$= \left[d\left[1 / r(\tau) \right] / d\tau \right] \int_{\alpha_{mn}}^{\alpha_{mx}} d_{B} \left[\alpha / r(\tau) \right] \alpha d_{A}(\alpha) d\alpha$$

as shown in Eq. (8.2) of Ref. [8]. Sampling-based procedures for the estimation of $CDF_P(p | [t_{mn}, t_{mx}])$ are described in Sect. 6 of Ref. [8], and integral-based representations for $CDF_P(p | [t_{mn}, t_{mx}])$ are derived in Sects. 4 and 5 of Ref. [8] for the following two cases: (i) $\overline{p}(t)$ increasing and $\overline{q}(t)$ decreasing, and (ii) $\overline{p}(t)$ increasing and $\overline{q}(t)$ constant-valued. The CDFs for link property at time of link failure for the four links defined in Table 1 and illustrated in Fig. 1 are shown in Fig. 2b.

The CDFs for the time at which LOAS occurs are defined by the probabilities summarized in Table 2 for the four indicated failure patterns. Specifically, Table 2 shows representations for PLOAS as functions $pF_i(t)$ of time (i.e., $pF_i(t)$ is the probability that LOAS occurs by time t for failure pattern i). The listed verification tests are the outcomes of assigning the same properties to all links as developed and described in Ref. [61]. The representations in Table 2 are derived and extensively illustrated in Ref. [7]. The CDFs for the time at which LOAS occurs for the four links defined in Table 1 and illustrated in Fig. 1 are shown in Fig. 3.

Table 2 Representation of Time-Dependent Values $pF_i(t)$, i = 1, 2, 3, 4, for PLOAS and Associated Verification Tests for Alternate Definitions of LOAS for WL/SL Systems with (i) *nWL* WLs and *nSL* SLs and (ii) independent distributions for link failure time ([62], Table 10).

Fig. 3 Illustration of the CDFs $pF_i(t)$, i = 1, 2, 3, 4, defined in Table 2 for the time at which LOAS occurs for the four links defined in Table 1.

4. CDFs for Failure Time Margins

4.1 Preliminaries: CDFs for Failure Time Margins. Suppose nL > 2 potentially mixed links (i.e., all WLs, all SLs, or a mixture of WLs and SLs) are under consideration with $CDF_{Tk}(\tau)$, k = 1, 2, ..., nL, the failure time CDF for link k (i.e., $CDF_{Tk}(\tau)$ is the probability that link k fails at or before time τ). Then, under the assumption that the link failure times are independent,

$$pLLF(t) = \sum_{k=1}^{nL} \left(\int_{t_{mn}}^{t} \left\{ \prod_{l=1,l\neq k}^{nL} CDF_{Tl}(\tau) \right\} dCDF_{Tk}(\tau) \right)$$

$$= \prod_{k=1}^{nL} CDF_{Tl}(t)$$
(4.1)

and

$$pFLF(t) = \sum_{k=1}^{nL} \left\{ \int_{t_{mn}}^{t} \left\{ \prod_{l=1,l\neq k}^{nL} \left[1 - CDF_{Tl}(\tau) \right] \right\} dCDF_{Tk}(\tau) \right\}$$

$$= 1 - \prod_{l=1}^{nL} \left[1 - CDF_{Tl}(t) \right],$$
(4.2)

where pLLF(t) is the probability that the last link failure occurs at or before time t and pFLF(t) is the probability that the first link failure occurs at or before time t. The initial definitions for pLLF(t) and pFLF(t) are the same as the definitions for $pF_1(t)$ and $pF_2(t)$, respectively, in Table 2 with the WL CDFs assumed to always have a value of 0 (i.e., $CDF_{T,WL,j}(\tau) = 0$ for all values of τ). The second definitions follow directly from the definitions of the CDFs $CDF_{Tk}(\tau)$. The equivalence of the pairs of definitions for pLLF(t) and pFLF(t) can be directly established but the notation becomes very complex for nL > 2.

Distributions for time margins corresponding to the difference between time when the failure of WLs deactivate a system and the failure of SLs result in LOAS can be calculated for the four WL/SL failure patterns defined in Table 2 with the use of results of the form shown in Eqs. (4.1) and (4.2).

4.2 Formal Representation: CDFs for Failure Time Margins. For a particular WL/SL configuration (i.e., one of the failure patterns defined in Table 2) let (i) $CDF_{T,WL}(t_{WL})$ be the CDF defined on the interval $[t_{mn}, t_{mx}]$ for the time t_{WL} when the failure of the system WLs potentially deactivates the system and (ii) $CDF_{T,SL}(t_{SL})$ be the CDF defined on the interval $[t_{mn}, t_{mx}]$ for the time t_{SL} when the failure of the system SLs potentially results in LOAS. The modifier "potentially" appears in the preceding sentence because the indicated failures may or may not have the indicated effect because of the timing of the WL and SL failures.

The desired distribution for the margin *m* defined by $t_{SL} - t_{WL}$ is given by

$$CDF_{TM} (m | [t_{mn}, t_{mx}]) = prob(t_{SL} - t_{WL} \le m)$$

$$= \lim_{n \to \infty} \sum_{i=1}^{n} CDF_{T,SL} (m + t_i) \Delta CDF_{T,WL} (t_i)$$

$$= \int_{t_{mn}}^{t_{mx}} CDF_{T,SL} (m + t) dCDF_{T,WL} (t)$$

$$= \int_{t_{mn}}^{t_{mx}} CDF_{T,SL} (m + t) [dCDF_{T,WL} (t)/dt] dt,$$
(4.3)

where t_i , $i = 0, 1, \dots, n$, is a subdivision of $[t_{mn}, t_{mx}]$. In effect, the result in Eq. (4.3) corresponds to the convolution of two probability distributions (e.g., see ([63], p.53).

The manners in which $CDF_{T,WL}(t_{WL})$ and $CDF_{T,SL}(t)$ are defined for the failure patterns in Table 2 are as follows for a WL/SL system with *nWL* WLs and *nSL* SLs:

Failure Pattern 1:
$$CDF_{T,WL}(t_{WL}) = pFLF(t_{WL})$$
 in Eq. (4.2)
 $CDF_{T,SL}(t_{SL}) = pLLF(t_{SL})$ in Eq. (4.1),
$$(4.4)$$

Failure Pattern 2:
$$CDF_{T,WL}(t_{WL}) = pFLF(t_{WL})$$
 in Eq. (4.2)
 $CDF_{T,SL}(t_{SL}) = pFLF(t_{SL})$ in Eq. (4.2), (4.5)

Failure Pattern 3:
$$CDF_{T,WL}(t_{WL}) = pLLF(t_{WL})$$
 in Eq. (4.1)
 $CDF_{T,SL}(t_{SL}) = pLLF(t_{SL})$ in Eq. (4.1), (4.6)

Failure Pattern 4:
$$CDF_{T,WL}(t_{WL}) = pLLF(t_{WL})$$
 in Eq. (4.1)
 $CDF_{T,SL}(t_{SL}) = pFLF(t_{SL})$ in Eq. (4.2). (4.7)

Examples of the link system failure probabilities $CDF_{T,WL}(t_{WL}) = pFLF(t_{WL})$, $CDF_{T,WL}(t_{WL}) = pLLF(t_{WL})$, $CDF_{T,SL}(t_{SL}) = pFLF(t_{SL})$ and $CDF_{T,SL}(t_{SL}) = pLLF(t_{SL})$ for the two SLs and two WLs defined and illustrated in Table 1 and Fig. 1 are presented in Fig. 4a. The values for pLLF(t) and pFLF(t) were obtained as indicated in Eqs. (4.1) and (4.2) by the multiplication of link failure time CDFs (see Eq. (3.1)) calculated by the CPLOAS program [64; 65].

Fig. 4 Failure time margins for (i) the four failure patterns resulting in LOAS indicated in Eqs. (4.4)-(4.7) and (ii) the system of four links defined and illustrated in Table 1 and Fig. 1 with $[t_{mn}, t_{mx}] = [0, 200]$: (a) link system failure probabilities $CDF_{T,WL}(t_{WL}) = pFLF(t_{WL})$, $CDF_{T,WL}(t_{WL}) = pLLF(t_{WL})$, $CDF_{T,SL}(t_{SL}) = pFLF(t_{SL})$ and $CDF_{T,SL}(t_{SL}) = pLLF(t_{SL})$ with pLLF(t) and pFLF(t) defined in Eqs. (4.1)-(4.2), and (b) failure time margins $CDF_{TM,i}(m | [t_{mn}, t_{mx}])$ for failure pattern i, i = 1, 2, 3, 4, defined in Eq. (4.3).

An illustration of the calculation of failure time margins $CDF_{TM,i}(m | [t_{mn}, t_{mx}]), i = 1,2,3,4,$ for failure pattern *i* in Table 2 with the use of quadrature-based procedures to evaluate the final integral in Eq. (4.3) is presented in Fig. 4b. Specifically, the margin results in Fig. 4b were obtained for the system of two SLs and two WLs defined and illustrated in Table 1 and Fig. 1 with use of procedures contained in the MATLAB numerical package [66] as summarized below. For a given failure pattern, the corresponding CDFs $CDF_{T,WL}(t_{WL})$ and $CDF_{T,SL}(t_{SL})$ indicated in Eqs. (4.4)-(4.7) and illustrated in Fig. 4a were (i) evaluated for 500 evenly spaced times from the interval [0, 200] and (ii) then approximated with the spline and ppval functions to obtain the spline approximations $spCDF_{T,SL}(t_{SL})$ and $spCDF_{T,WL}(t_{WL})$. Next, $dCDF_{T,WL}(t_{WL})/dt_{WL}$ was obtained by differentiating $spCDF_{T,WL}(t_{WL})$ with the **fnder** function to obtain the derivative $derCDF_{T,WL}(t_{WL})$. Then, the product $spCDF_{T,SL}(m+t_{WL})derCDF_{T,WL}(t_{WL})$ was integrated over $[t_{mn}, t_{mx}] = [0, 200]$ with the **integral** function to numerically evaluate the final integral in Eq. (4.3). Specifically, the indicated calculations were performed for 100 evenly spaced values of m from the interval [-100,100] to obtain the CDFs $CDF_{TM,i}(m | [t_{mn}, t_{mx}]), i =$ 1,2,3,4, for failure pattern *i* in Fig. 4b.

A brief elaboration on the nature of the results in Fig. 4 follows. As discussed in Ref. [67] and illustrated in Fig. 4, the performance of a WL/SL system under accident conditions can be viewed as a competing failure problem. In essence, there is a race to failure between the WL system and the SL system, with (i) the WL system winning the race if it fails before or at the same time as the SL system fails and (ii) the WL system losing the race if it fails after the SL system fails. The margin m of winning the race by the WL system is defined by

$$m = (\text{time } t_{SL} \text{ of SL system failure}) - (\text{time } t_{WL} \text{ of WL system failure})$$

= $t_{SL} - t_{WL}$, (4.8)

with a nonnegative margin corresponding to the WL system winning the race and a negative margin corresponding to the WL system losing the race. In the problem under consideration, the link system failure times t_{WL} and t_{SL} do not have fixed values but rather enter the analysis as distributions of values as a result of the aleatory uncertainty associated with the property values and failure values for the individual links.

The results in Fig. 4 are for 4 WL/SL systems, each with: (i) 2 WLs and 2 SLs, (ii) one of 2 possible definitions for WL system failure (i.e., first link to fail or last link to fail), and (iii) one of 2 possible definitions for SL system failure (i.e., first link to fail or last link to fail). As illustrated in Fig. 4a, this results in (i) distributions (i.e., CDFs)

$$CDF_{T,WL}(t_{WL}) = pLLF(t_{WL})$$
 and $CDF_{T,WL}(t_{WL}) = pFLF(t_{WL})$ (4.9)

for WL system failure time t_{WL} and (ii) distributions

$$CDF_{T,SL}(t_{SL}) = pLLF(t_{SL})$$
 and $CDF_{T,SL}(t_{SL}) = pFLF(t_{SL})$ (4.10)

for SL system failure time. The indicated CDFs are obtained as indicated in Sect. 4.1.

In turn as illustrated in Fig. 4b, the 4 WL/SL systems and their associated CDFs for link system failure time result in the following distributions (i.e., CDFs) for the failure time margin m in Eq. (4.8):

$$CDF_{T,WL}(t_{WL}) = pFLF(t_{WL}), CDF_{T,SL}(t_{SL}) = pLLF(t_{SL}) \rightarrow CDF_{TM,1}(m | [t_{mn}, t_{mx}]),$$
 (4.11)

$$CDF_{T,WL}(t_{WL}) = pFLF(t_{WL}), CDF_{T,SL}(t_{SL}) = pFLF(t_{SL}) \rightarrow CDF_{TM,2}(m | [t_{mn}, t_{mx}]),$$
 (4.12)

$$CDF_{T,WL}(t_{WL}) = pLLF(t_{WL}), CDF_{T,SL}(t_{SL}) = pLLF(t_{SL}) \rightarrow CDF_{TM,3}(m \mid [t_{mn}, t_{mx}]),$$
(4.13)

$$CDF_{T,WL}(t_{WL}) = pLLF(t_{WL}), CDF_{T,SL}(t_{SL}) = pFLF(t_{SL}) \rightarrow CDF_{TM,4}(m | [t_{mn}, t_{mx}]).$$
 (4.14)

The margin results $CDF_{TM,i}(m | [t_{mn}, t_{mx}]), i = 1, 2, 3, 4,$ in Eqs. (4.11)-(4.14) summarize the previously indicated "race" to failure for the 4 WL/SL systems under considerations and were

obtained by numerical evaluation of the integral in Eq. (4.3). As shown in Sects. 4.3 and 4.4. the CDFs $CDF_{TM,i}(m | [t_{mn}, t_{mx}]), i = 1, 2, 3, 4$, can also be obtained with sampling-based procedures.

4.3 Sampling-based Estimation of $CDF_{TM}(m | [t_{mn}, t_{mx}])$ **for Failure Time Margins.** A sampling-based determination of $CDF_{TM}(m | [t_{mn}, t_{mx}]) = prob(t_{SL} - t_{WL} \le m)$ is now considered. For this determination, the representation for $prob(t_{SL} - t_{WL} \le m)$ can be formulated as

$$prob_{i} (t_{SL} - t_{WL} \le m) = \int_{t_{mn}}^{t_{mx}} \int_{t_{mn}}^{t_{mx}} \delta_{m} (t_{SL} - t_{WL}) dCDF_{T,SL} (t_{SL}) dCDF_{T,WL} (t_{WL}) = \int_{t_{mn}}^{t_{mx}} \int_{t_{mn}}^{t_{mx}} \delta_{m} (t_{SL} - t_{WL}) d_{T,SL} (t_{SL}) d_{T,WL} (t_{WL}) dt_{SL} dt_{WL},$$
(4.15)

where (i) the subscripts i = 1, 2, 3, 4 indicate the definitions of $CDF_{T,SL}(t_{SL})$ and $CDF_{T,WL}(t_{WL})$ for Patterns 1-4 in Eqs. (4.4)-(4.7) and thus correspondingly for the four WL/SL failure patterns in Table 2, (ii) $d_{T,SL}(t_{SL})$ and $d_{T,WL}(t_{WL})$ are the density functions associated with $CDF_{T,SL}(t_{SL})$ and $CDF_{T,WL}(t_{WL})$, and (iii)

$$\delta_m \left(t_{SL} - t_{WL} \right) = \begin{cases} 1 & \text{if } t_{SL} - t_{WL} < m \\ 0 & \text{otherwise.} \end{cases}$$
(4.16)

In turn, the approximation

$$prob_{i}\left(t_{SL}-t_{WL}\leq m\right) \cong \sum_{r=1}^{n} \delta_{m}\left(t_{SL,r}-t_{WL,r}\right) / n \tag{4.17}$$

results for a random sample $[t_{SL,r}, t_{WL,r}]$, r = 1, 2, ..., n, from $[t_{mn}, t_{mx}] \times [t_{mn}, t_{mx}]$ obtained with use of $CDF_{T,SL}(t_{SL})$ and $CDF_{T,WL}(t_{WL})$.

Another possibility is to generate a sample of individual link failure times

$$\mathbf{s}_{r} = [tWL_{1r}, tWL_{2r}, \cdots, tWL_{nWL, r}, tSL_{1r}, tSL_{2r}, \cdots, tSL_{nSL, r}], r = 1, 2, \cdots, n,$$
(4.18)

directly from the corresponding link failure time CDFs and then define margins by

$$m_{i}(\mathbf{S}_{r}) = \begin{cases} \max\{tSL_{1r}, tSL_{2r}, \cdots, tSL_{nSL,r}\} - \min\{tWL_{1r}, tWL_{2r}, \cdots, tWL_{nWL,r}\} & \text{for } i = 1 \\ \min\{tSL_{1r}, tSL_{2r}, \cdots, tSL_{nSL,r}\} - \min\{tWL_{1r}, tWL_{2r}, \cdots, tWL_{nWL,r}\} & \text{for } i = 2 \\ \max\{tSL_{1r}, tSL_{2r}, \cdots, tSL_{nSL,r}\} - \max\{tWL_{1r}, tWL_{2r}, \cdots, tWL_{nWL,r}\} & \text{for } i = 3 \\ \min\{tSL_{1r}, tSL_{2r}, \cdots, tSL_{nSL,r}\} - \max\{tWL_{1r}, tWL_{2r}, \cdots, tWL_{nWL,r}\} & \text{for } i = 3 \\ \min\{tSL_{1r}, tSL_{2r}, \cdots, tSL_{nSL,r}\} - \max\{tWL_{1r}, tWL_{2r}, \cdots, tWL_{nWL,r}\} & \text{for } i = 4 \end{cases}$$

$$= \begin{cases} \overline{tSL}_{k(r),r} - \underline{tWL}_{l(r),r} & \text{for } i = 1 \\ \underline{tSL}_{k(r),r} - \underline{tWL}_{l(r),r} & \text{for } i = 3 \\ \underline{tSL}_{k(r),r} - \underline{tWL}_{l(r),r} & \text{for } i = 3 \\ \underline{tSL}_{k(r),r} - \underline{tWL}_{l(r),r} & \text{for } i = 3 \\ \underline{tSL}_{k(r),r} - \underline{tWL}_{l(r),r} & \text{for } i = 4 \end{cases}$$

$$(4.19)$$

with (i) *i* indicating Patterns 1-4 in Eqs. (4.4)-(4.7) and, correspondingly, the four WL/SL failure patterns in Table 2, (ii) underscores and overscores indicating minimums and maximums, respectively, and (iii) the subscripts k(r) and l(r) identifying the links that failed at the indicated times. Specifically, k(r) identifies the SL whose failure potentially results in LOAS, and l(r) identifies the WL whose failure potentially prevents LOAS. Then,

$$prob_{i}\left(t_{SL}-t_{WL}\leq m\right)\cong\sum_{r=1}^{n}\delta_{m}\left[m_{i}\left(\mathbf{s}_{r}\right)\right]/n$$
(4.20)

with $\delta_m[m_i(\mathbf{s}_r)]$ defined as in Eq. (4.16).

Yet another sampling approach is to (i) sample the defining parameters for the individual links (i.e., the α 's and β 's) in consistency with their specified distributions as defined by the density functions $d_A(\alpha)$ and $d_B(\beta)$ for the individual links and (ii) then determine the resultant margins. Specifically, a sample

$$\mathbf{p}_{r} = \left[\mathbf{pWL}_{1r}, \mathbf{pWL}_{2r}, \cdots, \mathbf{pWL}_{nWL, r}, \mathbf{pSL}_{1r}, \mathbf{pSL}_{1r}, \cdots, \mathbf{pSL}_{nSL, r}\right], r = 1, 2, \cdots, n$$
(4.21)

with

$$\mathbf{pWL}_{lr} = \left[\alpha_{WL,lr}, \beta_{WL,lr}\right] \text{ for } l = 1, 2, \cdots, nWL$$
(4.22)

and

$$\mathbf{pSL}_{lr} = \left[\alpha_{SL,lr}, \beta_{SL,lr}\right] \text{ for } l = 1, 2, \cdots, nSL$$
(4.23)

is generated from the distributions of the α 's and β 's for the individual links. Next, the link failure times in Eq. (4.18) are determined as functions

$$tWL_{lr} = tWL_{lr} \left(\mathbf{pWL}_{lr} \right) = tWL_{lr} \left(\alpha_{WL,lr}, \beta_{WL,lr} \right) \text{ for } l = 1, 2, \cdots, nWL$$
(4.24)

and

$$tSL_{lr} = tSL_{lr} \left(\mathsf{pSL}_{lr} \right) = tSL_{lr} \left(\alpha_{SL,lr}, \beta_{SL,lr} \right) \text{ for } l = 1, 2, \cdots, nSL$$

$$(4.25)$$

of elements of the sampled vectors \mathbf{p}_r in Eq. (4.21). At this point, $prob_i(t_{SL} - t_{WL} \le m)$ can be determined as indicated in Eqs. (4.19)-(4.20) with the redefinition of the elements of \mathbf{p}_r described in Eqs. (4.24)-(4.25).

A more mathematically explicit description of the use of sampling-based procedures in WL/SL analyses is given in Sect. 5 of Ref. [7]. This section also describes the use of importance sampling in WL/SL analyses.

4.4 Verification Results for $CDF_{TM}(m | [t_{nm}, t_{mx}])$ **for Failure Time Margins.** As a verification test, Fig. 5 provides a comparison of $CDF_{TM,i}(m | [t_{nm}, t_{mx}])$ for failure pattern *i*, *i* = 1, 2, 3, 4, calculated with (i) version 2.10 of the CPLOAS program [64; 65], the second sampling-based procedure indicated in Eqs. (4.18)-(4.20), and a sample of size $n = 10^6$ and (ii) the quadrature-based procedure described in Sect. 4.2. The sampling-based results in Fig. 5 are essentially the same as the quadrature-based results in Fig. 4b. Further, careful comparison of the quadrature-based CDFs in Fig. 4b and the sampling-based CDFs in Fig. 5 shows that corresponding CDFs almost exactly overlay. In addition to a visual comparison of the results in Fig. 4 and Fig. 5, a formal comparison based on root mean square error (RMSE) produced RMSEs of 5E-04, 2E-04, 3E-04 and 2E-04 for failure patterns 1, 2, 3 and 4. This level of agreement provides a strong verification that the procedures for obtaining $CDF_{TM}(m | [t_{nm}, t_{mx}])$ described in Sects. 4.2 and 4.3 are correct in both (i) mathematical development and (ii) computational implementation.

Fig. 5 Verification results for failure time margins $CDF_{TM,i}(m | [t_{mn}, t_{mx}]), i = 1, 2, 3, 4$, obtained with quadrature-based procedures (see Sect. 4.2) and sampling-based procedures (see Eqs. (4.21) -(4.25) in Sect. 4.3) for (i) the four failure patterns resulting in LOAS indicated in Eqs. (4.4)-(4.7) and (ii) the system of four links defined and illustrated in Table 1 and Fig. 1 with $[t_{mn}, t_{mx}] = [0, 200]$.

4.5 Connection Between Failure Time Margins $CDF_{TM,i}(0|[t_{mn},t_{mx}])$, i = 1, 2, 3, 4, and **PLOAS.** The probabilities $CDF_{TM,i}(0|[t_{mn},t_{mx}])$, i = 1, 2, 3, 4, associated with the failure time margin m = 0 defined in conjunction with Eq. (4.3) are equal to the probabilities $pF_i(t_{mx})$, i = 1, 2, 3, 4, for LOAS defined in Table 2 and illustrated in Fig. 3. Specifically,

$$pF_{i}(t_{mx}) = CDF_{TM,i}(0 | [t_{mn}, t_{mx}]) = \int_{t_{mn}}^{t_{mx}} CDF_{T,SL}(t_{WL}) dCDF_{T,WL}(t_{WL})$$
(4.26)

for i = 1, 2, 3, 4 with the appropriate values for $CDF_{T,SL}(t_{WL})$ and $CDF_{T,WL}(t_{WL})$ for failure pattern *i* defined in Eqs. (4.4)-(4.7). This connection is (i) illustrated by the equality of $pF_i(200)$

and $CDF_{TM,i}(0|[0,200])$ in Fig. 3 and Fig. 4b and (ii) provides an additional verification result that the failure time margins in Figs. 4 and 5 have been calculated correctly.

5. CDFs for System Property Values at LOAS

5.1 Formal Representation: System Involving Only One Type of Link. In the analysis of a system with multiple components, it is important to examine both (i) the combined performance of the components and (ii) the performance of the individual components. This examination provides important insights with respect to the overall performance of the system and also has the potential to identify errors or inefficiencies in the sub analyses associated with individual components that are not recognized in an examination of the final results obtained in an analysis of the complete system. For this reason, the analysis of a WL/SL system should include analyses of (i) the individual links, (ii) the WL system and the SL system, and (iii) the combined system of WLs and SLs. The analysis of individual links is extensively discussed in Ref. [8]. The representations for link system failure times developed in Sect. 4.1 are examples of analysis results that can be obtained for WL systems and SL systems and that will later support full system analyses. Finally, the analysis of a combined system of WLs and SLs is exemplified by the analyses for WL/SL system failure time in Ref. [7] and the various margin results for WL/SL systems developed in this presentation.

Representations for the distribution of link property values at link system failure are developed in this section and provide another example of a result that can be used in the analysis of WL systems and SL systems. In addition, these representations will be used in the development of (i) distributions in Sect. 5.4 for the property value at link failure for the SL whose failure results in LOAS for a system with multiple WLs and SLs and (ii) distributions in Sect. 6 for margins based on WL and SL property values.

A system involving only one type of link is considered in this section (i.e., only WLs or only SLs). Further, the links comprising the indicated system must have the same type of failure property. For example, all links failing on the basis of temperature or all links failing on the basis of pressure are acceptable possibilities. However, some links failing on the basis of temperature and other links failing on the basis of pressure is not acceptable. Consistent with the failure modes in Table 2, two failure possibilities are considered: (i) system failure occurs at the time of the last link failure, and (ii) system failure occurs at the time of the first link failure.

As in Sect. 4, *nL* links are under consideration with failure time CDFs $CDF_{Tk}(\tau)$, k = 1, 2, ..., nL. Further, as developed in Sect. 9 of Ref. [8],

$$CDF_{Pk}(p \mid \tau) = \text{ probability that link } k \text{ fails at a property value } \leq p \text{ conditional on}$$

failure of link k at time τ
$$= \int_{p_{mn,k}(\tau)}^{p_{mx,k}(p,\tau)} d_{Pk}(\tilde{p} \mid \tau) d\tilde{p},$$
(5.1)

where (i) $d_{Pk}(\tilde{p} | \tau)$ is the density function corresponding to $CDF_{Pk}(p | \tau)$ defined in Eq. (9.63) and Table 6 of Ref. [8], (ii) $[p_{mn,k}(\tau), p_{mx,k}(\tau)]$ is the interval of property values at which link k could fail at time τ (see Table 3) and thus corresponds to the sample space associated with $d_{Pk}(\tilde{p} | \tau)$, and (iii) $p_{mx,k}(p,\tau) = \min\{p, p_{mx,k}(\tau)\}$. Given the preceding, replacement of $dCDF_{Tk}(\tau)$ in Eqs. (4.1) and (4.2) by $CDF_{Pk}(p | \tau)dCDF_{Tk}(\tau)$ produces

$$CDF_{P,LLF}(p | [t_{mn}, t_{mx}]) = \text{ probability that last link failure occurs at} a property value $\leq p$ at a time $\tau \leq t_{mx}$

$$= \sum_{k=1}^{nL} \left(\int_{t_{mn}}^{t_{mx}} \left\{ \prod_{l=1,l\neq k}^{nL} CDF_{Tl}(\tau) \right\} CDF_{Pk}(p | \tau) dCDF_{Tk}(\tau) \right)$$

$$= \sum_{k=1}^{nL} \left(\int_{\tau_{mn,k}(p)}^{\tau_{mx,k}(t_{mx},p)} \left\{ \prod_{l=1,l\neq k}^{nL} CDF_{Tl}(\tau) \right\} \left\{ \int_{p_{mn,k}(\tau)}^{p_{mx,k}(p,\tau)} d_{Pk}(\tilde{p} | \tau) d\tilde{p} \right\} d_{Tk}(\tau) d\tau \right)$$

$$= \sum_{k=1}^{nL} \left(\int_{\tau_{mn,k}(p)}^{\tau_{mx,k}(t_{mx},p)} \left\{ \prod_{l=1,l\neq k}^{nL} CDF_{Tl}(\tau) \right\} \left\{ \int_{p_{mn,k}(\tau)}^{p_{mx,k}(p,\tau)} d_{Pk}(\tilde{p} | \tau) d_{Tk}(\tau) d\tilde{p} \right\} d\tau \right)$$
(5.2)$$

and, in like manner,

$$CDF_{P,FLF}(p | [t_{mn}, t_{mx}]) = \text{ probability that first link failure occurs at} a property value $\leq p$ at a time $\tau \leq t_{mx}$

$$= \sum_{k=1}^{nL} \left\{ \int_{t_{mn}}^{t_{mx}} \left\{ \prod_{l=1, l \neq k}^{nL} \left[1 - CDF_{Tl}(\tau) \right] \right\} CDF_{Pk}(p | \tau) dCDF_{Tk}(\tau) \right\}$$

$$= \sum_{k=1}^{nL} \left\{ \int_{\tau_{mn,k}(p)}^{\tau_{mx,k}(t_{mx},p)} \left\{ \prod_{l=1, l \neq k}^{nL} \left[1 - CDF_{Tl}(\tau) \right] \right\} \left\{ \int_{p_{mn,k}(\tau)}^{p_{mx,k}(p,\tau)} d_{Pk}(\tilde{p} | \tau) d_{Tk}(\tau) d\tilde{p} \right\} d\tau \right\}$$
(5.3)$$

with (i) $CDF_{p_k}(p \mid \tau)$ replaced by the representation in Eq. (5.1), (ii) $dCDF_{T_k}(\tau)$ replaced by $d_{T_k}(\tau)d\tau$ with $d_{T_k}(\tau) = dCDF_k(\tau)/d\tau$ as defined in Eq. (8.2) of Ref. [8] and subsequently defined in more detail in Eq. (9.64) of Ref. [8], (iii) $\tau_{mx,k}(t_{mx}, p) = \min\{t_{mx}, \tau_{mx,k}(p)\}$ with $\tau_{mx,k}(p) = \text{last time at which link } k \text{ can fail at a property value } \leq p$, and (iv) the integral over $[t_{mn}, t_{mx}]$ equal to 0 for link k and $t_{mx} \leq \tau_{mn,k}(p)$ with $\tau_{mn,k}(p) = \text{first time at which link } k \text{ can fail at a property value } \leq p$.

Table 3 Integration limits associated with a link in Eqs. (5.1)-(5.6) with $\overline{p}(\tau)$ increasing and $\overline{q}(\tau)$ either decreasing or constant-valued (adapted from Ref. [8], Table 7).

The definitions of the density functions $d_{Pk}(\tilde{p} | \tau)$ and $d_{Tk}(\tau)$ are complicated (see Eqs. (9.63) and (9.64) in Ref. [8]). However, some simplification occurs when the product $d_{Pk}(\tilde{p} | \tau)d_{Tk}(\tau)$ is involved, as is the case in Eqs. (5.2) and (5.3). Specifically,

$$d_{Pk}(\tilde{p} \mid \tau) d_{Tk}(\tau) = \left\{ d \left[\frac{1}{r_k(\tau)} \right] / d\tau \right\} \left\{ \frac{\tilde{p}}{\bar{p}_k^2(\tau)} \right\} d_{Ak} \left[\tilde{p} / \bar{p}_k(\tau) \right] d_{Bk} \left[\tilde{p} / \bar{q}_k(\tau) \right]$$
(5.4)

as developed in conjunction with Eqs. (9.63), (9.64) and (9.65) of Ref. [8]. In turn, replacement of $d_{Pk}(\tilde{p} | \tau) d_{Tk}(\tau)$ in Eqs. (5.2) and (5.3) with the preceding form produces the representations

$$CDF_{P,LLF}\left(p \mid [t_{mn}, t_{mx}]\right) = \sum_{k=1}^{nL} \left(\int_{\tau_{mn,k}(p)}^{\tau_{mx,k}(t_{mx},p)} \left\{ \prod_{l=1,l\neq k}^{nL} CDF_{Tl}\left(\tau\right) \right\} \left\{ d\left[\frac{1}{t_{k}(\tau)}\right] / d\tau \right\} \right.$$

$$\times \left\{ \int_{p_{mn,k}(\tau)}^{p_{mx,k}(p,\tau)} \left\{ \frac{\tilde{p}}{\bar{p}_{k}^{2}(\tau)} \right\} d_{Ak}\left[\tilde{p} / \bar{p}_{k}(\tau)\right] d_{Bk}\left[\tilde{p} / \bar{q}_{k}(\tau)\right] d\tilde{p} \right\} d\tau \right)$$
(5.5)

and

$$CDF_{P,FLF}(p | [t_{mn}, t_{mx}]) = \sum_{k=1}^{nL} \left(\int_{\tau_{mn,k}(p)}^{\tau_{mx,k}(t_{mx},p)} \left\{ \prod_{l=1,l\neq k}^{nL} [1 - CDF_{Tl}(\tau)] \right\} \left\{ d\left[\frac{1}{r_{k}(\tau)}\right] / d\tau \right\} \\ \times \left\{ \int_{p_{mn,k}(\tau)}^{p_{mx,k}(p,\tau)} \left\{ \frac{\tilde{p}}{\bar{p}_{k}^{2}(\tau)} \right\} d_{Ak} \left[\tilde{p} / \bar{p}_{k}(\tau) \right] d_{Bk} \left[\tilde{p} / \bar{q}_{k}(\tau) \right] d\tilde{p} \right\} d\tau \right)$$
(5.6)

for $CDF_{P,LLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,FLF}(p | [t_{mn}, t_{mx}])$ with the integral over $[t_{mn}, t_{mx}]$ equal to 0 for link k and $t_{mx} \leq \tau_{mn,k}(p)$. Although the representations for $CDF_{P,LLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,FLF}(p | [t_{mn}, t_{mx}])$ in Eqs. (5.5) and (5.6) are complicated, they are numerically simpler than the representations in Eqs. (5.2) and (5.3) due to the significant complexity in the definitions of $CDF_{Pk}(p | \tau)$ and $d_{Tk}(\tau)$.

For future use, it is noted that a derivation for the equality

$$CDF_{p_{k}}(p \mid \tau)d_{Tk}(\tau)d\tau = \left\{ \int_{p_{mn,k}(\tau)}^{p_{mx,k}(p,\tau)} d_{p_{k}}(\tilde{p} \mid \tau)d_{Tk}(\tau)d\tilde{p} \right\} d\tau$$

$$= \left\{ \int_{p_{mn,k}(\tau)}^{p_{mx,k}(p,\tau)} \left\{ d\left[\frac{1}{r_{k}(\tau)}\right] / d\tau \right\} \left\{ \frac{\tilde{p}}{\bar{p}_{k}^{2}(\tau)} \right\} d_{Ak}\left[\tilde{p} / \bar{p}_{k}(\tau)\right] d_{Bk}\left[\tilde{p} / \bar{q}_{k}(\tau)\right] d\tilde{p} \right\} d\tau \qquad (5.7)$$

$$= \left\{ d\left[\frac{1}{r_{k}(\tau)}\right] / d\tau \right\} \left\{ \int_{p_{mn,k}(\tau)}^{p_{mx,k}(p,\tau)} \left\{ \frac{\tilde{p}}{\bar{p}_{k}^{2}(\tau)} \right\} d_{Ak}\left[\tilde{p} / \bar{p}_{k}(\tau)\right] d_{Bk}\left[\tilde{p} / \bar{q}_{k}(\tau)\right] d\tilde{p} \right\} d\tau \qquad (5.7)$$

is embedded in the derivations leading to Eqs. (5.5) and (5.6).

As examples, CDFs for property value at link system failure (i.e., $CDF_{P,LLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,FLF}(p | [t_{mn}, t_{mx}])$ with $[t_{mn}, t_{mx}] = [0, 200]$) for systems with two WLs and systems with two SLs links defined with the WLs and SLs described and illustrated in Table 1 and Fig. 1 are presented in Fig. 6. With respect to notation,

$$CDF_{P,WL,LLF}(p | [t_{mn}, t_{mx}]) = CDF_{P,LLF}(p | [t_{mn}, t_{mx}]) \text{ for WL systems,}$$

$$CDF_{P,WL,FLF}(p | [t_{mn}, t_{mx}]) = CDF_{P,FLF}(p | [t_{mn}, t_{mx}]) \text{ for WL systems,}$$

$$CDF_{P,SL,LLF}(p | [t_{mn}, t_{mx}]) = CDF_{P,LLF}(p | [t_{mn}, t_{mx}]) \text{ for SL systems,}$$

$$(5.8)$$

$$(5.9)$$

$$(5.9)$$

$$CDF_{P,SL,FLF}(p \mid [t_{mn}, t_{mx}]) = CDF_{P,FLF}(p \mid [t_{mn}, t_{mx}]) \text{ for SL systems.}$$
(5.11)

Quadrature-based evaluation of the defining integrals in Eqs. (5.5) and (5.6) for $CDF_{P,LLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,FLF}(p | [t_{mn}, t_{mx}])$ was performed with the MATLAB numerical package [66] and the integration program **TwoD**, which is documented in Ref. [60] and available from Prof. Shampine's website (<u>http://faculty.smu.edu/shampine/current.html</u>). The **TwoD** function was selected for use because it offered greater flexibility in defining limits of integration than the Matlab functions **dblquad** and **integral2**. In the development of the integrands for Eqs. (5.5) and (5.6), (i) representations for the density functions $d_{Ak}(\alpha)$ and $d_{Bk}(\beta)$ were obtained with use of the **makedist** and **pdf** functions, (ii) the representation for the derivative was obtained with use of the **diff** and **matlabFunction** functions, and (iii) representations for the expressions involving products of CDFs were obtained with use of the **spline** function."

Fig. 6 Property value at link system failure CDFs (i.e., $CDF_{P,WL,LLF}(p | [t_{mn}, t_{mx}])$, $CDF_{P,WL,FLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,SL,FLF}(p | [t_{mn}, t_{mx}])$ with $[t_{mn}, t_{mx}] = [0, 200]$) obtained by quadrature-based evaluation of the integrals in Eqs. (5.5) and (5.6) for systems with two WLs and systems with two SLs links defined with the WLs and SLs described and illustrated in Table 1 and Fig. 1.

The double integrals in Eqs. (5.5) and (5.6) have time τ as the outer variable of integration and property value p as the inner variable of integration. If desired, the integrals in Eqs. (5.5) and (5.6) can be rewritten with p as the outer variable of integration and τ as the inner variable of integration.

Another possibility is to remove the term $\tilde{p} / \bar{p}_k^2(\tau)$ in Eqs. (5.5) and (5.6) through the change of variables $\alpha_k(\tilde{p}) = \tilde{p} / \bar{p}_k(\tau)$. This produces the representations

$$CDF_{P,LLF}(p | [t_{mn}, t_{mx}]) = \sum_{k=1}^{nL} \left(\int_{\tau_{mn,k}(p)}^{\tau_{mx,k}(t_{mx},p)} \left\{ \prod_{l=1,l\neq k}^{nL} CDF_{Tl}(\tau) \right\} \left\{ d\left[\frac{1}{r_{k}(\tau)}\right] / d\tau \right\} \times \left\{ \int_{p_{mn,k}(\tau)/\overline{p}_{k}(\tau)}^{p_{mx,k}(p,\tau)/\overline{p}_{k}(\tau)} \alpha d_{Ak}(\alpha) d_{Bk} \left[\alpha / r_{k}(\tau) \right] d\alpha \right\} d\tau \right)$$
(5.12)

and

$$CDF_{P,FLF}\left(p \mid [t_{mn}, t_{mx}]\right) = \sum_{k=1}^{nL} \left(\int_{\tau_{mn,k}(p)}^{\tau_{mx,k}(t_{mx},p)} \left\{ \prod_{l=1,l\neq k}^{nL} \left[1 - CDF_{Tl}\left(\tau\right) \right] \right\} \left\{ d\left[\frac{1}{r_{k}\left(\tau\right)} \right] / d\tau \right\} \\ \times \left\{ \int_{p_{mn,k}(\tau)/\overline{p}_{k}(\tau)}^{p_{mx,k}\left(p,\tau\right)/\overline{p}_{k}(\tau)} \alpha d_{Ak}\left(\alpha\right) d_{Bk}\left[\alpha / r_{k}(\tau) \right] d\alpha \right\} d\tau \right\}$$
(5.13)

for $CDF_{P,LLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,FLF}(p | [t_{mn}, t_{mx}])$ with the integral over $[t_{mn}, t_{mx}]$ equal to 0 for link k and $t_{mx} \le \tau_{mn,k}(p)$.

5.2 Sampling-based Estimation of $CDF_{P,LLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,FLF}(p | [t_{mn}, t_{mx}])$. Another possibility is to use a sampling-based procedure to estimate $CDF_{P,LLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,FLF}(p | [t_{mn}, t_{mx}])$. This procedure involves (i) generating a sample from the defining parameters for the individual links (i.e., the α 's and β 's) in consistency with their specified distributions as defined by the density functions $d_A(\alpha)$ and $d_B(\beta)$ for the individual links and (ii) then determining the resultant failure times and associated failure values. Specifically, a sample

$$\mathbf{p}_{r} = \left[\mathbf{pL}_{1r}, \mathbf{pL}_{2r}, \cdots, \mathbf{pL}_{nL, r}\right], r = 1, 2, \cdots, n$$
(5.14)

with

$$\mathbf{pL}_{lr} = \left[\alpha_{lr}, \beta_{lr}\right] \text{ for } l = 1, 2, \cdots, nL$$
(5.15)

is generated from the distributions of the α 's and β 's for the individual links. Next, the link failure times tL_{lr} and failure values pL_{lr} are determined as functions

$$tL_{lr} = tL_{lr} \left(\mathbf{pL}_{lr} \right) = tL_{lr} \left(\alpha_{lr}, \beta_{lr} \right)$$
(5.16)

and

$$pL_{lr} = pL_{lr}\left(\mathsf{pL}_{lr}\right) = pL_{lr}\left(\alpha_{lr}, \beta_{lr}\right) = \alpha_{lr}\overline{p}_{l}\left[tL_{lr}\left(\alpha_{lr}, \beta_{lr}\right)\right]$$
(5.17)

of elements of the sampled vectors \mathbf{p}_r in Eq. (5.14).

The following additional expressions for sample element \mathbf{p}_s are now introduced for use in estimating $CDF_{P,LLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,FLF}(p | [t_{mn}, t_{mx}])$:

$$tL_{f(s)} = \text{first link failure time for } \mathbf{p}_{s}$$

$$= \min\{tL_{1s}, tL_{2s}, \cdots, tL_{nL,s}\},$$

$$tL_{l(s)} = \text{last link failure time for } \mathbf{p}_{s}$$

$$= \max\{tL_{1s}, tL_{2s}, \cdots, tL_{nL,s}\},$$

$$pL_{f(s)} = \text{property value at first link failure for } \mathbf{p}_{s}$$

$$= \alpha_{f(s)} \overline{p}_{f(s)}(tL_{f(s)}),$$
(5.18)
(5.19)
(5.20)

$$pL_{l(s)} = \text{property value at last link failure for } \mathbf{p}_{s}$$
$$= \alpha_{l(s)} \overline{p}_{l(s)} (tL_{l(s)}), \qquad (5.21)$$

and

$$\delta(\tilde{t}, \tilde{p} | t_{mx}, p) = \begin{cases} 1 \text{ for } \tilde{t} \leq t_{mx} \text{ and } \tilde{p} \leq p \\ 0 \text{ otherwise.} \end{cases}$$
(5.22)

In turn,

$$CDF_{P,LLF}(p | [t_{mn}, t_{mx}]) \cong \sum_{s=1}^{n} \delta(tL_{l(s)}, pL_{l(s)} | t_{mx}, p) / n$$
(5.23)

and

$$CDF_{P,FLF}(p | [t_{mn}, t_{mx}]) \cong \sum_{r=1}^{n} \delta(tL_{f(s)}, pL_{f(s)} | t_{mx}, p) / n.$$
(5.24)

5.3 Verification Results for $CDF_{P,LLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,FLF}(p | [t_{mn}, t_{mx}])$. As a verification test, Fig. 7 presents a comparison of CDFs for property value at link system failure (i.e., $CDF_{P,LLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,FLF}(p | [t_{mn}, t_{mx}])$) for systems with two WLs and systems with two SLs links obtained by (i) quadrature-based evaluation of the integrals in Eqs. (5.5) and (5.6) as described in Sect. 5.1 and (ii) a sampling-based calculation as defined in Eqs. (5.23) and (5.24) performed with the CPLOAS program [64; 65] and a sample of size $n = 10^6$. The CDFs $CDF_{P,LLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,FLF}(p | [t_{mn}, t_{mx}])$ are not defined outputs of the

CPLOAS program but (i) these CDFs are calculated as indicated in Sect. 5.2 as part of the SL-SL margin analysis described in Sect. 7.3 and (ii) were obtained for this analysis by adding a few lines of code to CPLOAS to write them to a saved output file. The results obtained with the two evaluation procedures are essentially identical. This level of agreement provides a strong verification that the two procedures for obtaining $CDF_{P,LLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,FLF}(p | [t_{mn}, t_{mx}])$ are correct in both (i) mathematical development and (ii) computational implementation.

Fig. 7 Verification results for property value at link system failure (i.e., $CDF_{P,WL,LLF}(p | [t_{mn}, t_{mx}])$, $CDF_{P,WL,FLF}(p | [t_{mn}, t_{mx}])$, $CDF_{P,SL,LLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,SL,FLF}(p | [t_{mn}, t_{mx}])$ with $[t_{mn}, t_{mx}] = [0, 200]$) obtained with quadrature-based procedures (see Sect. 5.1) and sampling-based procedures (see Sect. 5.2) for systems with two WLs and systems with two SLs links defined with the WLs and SLs described and illustrated in Table 1 and Fig. 1.

5.4 Formal Representation: System Involving Multiple WLs and SLs. Distributions (i.e., CDFs) for SL system failure values (i.e., property value at link failure for SL whose failure results in LOAS) for systems involving multiple WLs and SLs have representations that are similar to the representations for $CDF_{P,LLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,FLF}(p | [t_{mn}, t_{mx}])$ developed in Sect. 5.1. As in Sect. 5.1, all SLs must have the same type of failure property (e.g., temperature for all SLs or pressure for all SLs). However, WLs do not have this restriction (e.g., some WLs could fail on the basis of temperature while other WLs fail on the basis of pressure). The starting points for these representations are the probabilities for LOAS in Table 2. For notational convenience, let

$$CDF_{P,SL,i}(p | [t_{mn}, t_{mx}]) =$$
 probability that LOAS occurs at a SL value $\leq p$ at a
time $\tau \leq t_{mx}$ for failure pattern $i = 1, 2, 3, 4$ defined in Table 2. (5.25)

Representations for $CDF_{P,SL,i}(p | [t_{mn}, t_{mx}])$, i = 1, 2, 3, 4, that are analogous to the representations for $CDF_{P,LLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,FLF}(p | [t_{mn}, t_{mx}])$ developed in in Eqs. (5.2)-(5.6) of Sect. 5.1 result by replacing $dCDF_{T,SL,k}(\tau)$ in the representations for $pF_1(t_{mx})$, $pF_2(t_{mx})$, $pF_3(t_{mx})$ and $pF_4(t_{mx})$ in Table 2 with

$$CDF_{P,SL,k}(p \mid \tau) dCDF_{T,SL,k}(\tau),$$
(5.26)

or equivalently, with

$$CDF_{P,SL,k}(p \mid \tau)d_{T,SL,k}d\tau = \left\{ d\left[\frac{1}{r_{k}(\tau)}\right] / d\tau \right\} \left\{ \int_{p_{mn,k}(\tau)}^{p_{mx,k}(p,\tau)} \left\{\frac{\tilde{p}}{\bar{p}_{k}^{2}(\tau)}\right\} d_{Ak}\left[\tilde{p} / \bar{p}_{k}(\tau)\right] d_{Bk}\left[\tilde{p} / \bar{q}_{k}(\tau)\right] d\tilde{p} \right\} d\tau$$

$$(5.27)$$

as defined in Eq. (5.7). Specifically, replacement of $dCDF_{T,SL,k}(\tau)$ with the expressions in Eqs. (5.26) and (5.27) produces the representations for $CDF_{P,SL,i}(p | [t_{mn}, t_{mx}]), i = 1, 2, 3, 4,$ summarized in Table 4.

Table 4 Representation of $CDF_{P,SL,i}(p | [t_{mn}, t_{mx}])$, i = 1, 2, 3, 4, for (i) SL system property at time of LOAS, (ii) *nWL* WLs and *nSL* SLs, (iii) independent distributions for link failure time, and (iv) the integral over $[t_{mn}, t_{mx}]$ equal to 0 for SL k and $t_{mx} \le \tau_{mn,k}(p)$ with $\tau_{mn,k}(p)$ and other integration limits defined in Table 3.

As an example, the CDFs $CDF_{P,SL,i}(p | [t_{mn}, t_{mx}])$, i = 1, 2, 3, 4, for SL property value at LOAS determined over all possible times of link failure as indicated in Table 4 are illustrated in Fig. 8. The results in Fig. 8 were obtained by use of numerical (i.e., quadrature) procedures to evaluate the integrals in Table 4 with the MATLAB program **TwoD** [68] in a manner similar to that described in Sect. 5.1.

Fig. 8 Property value of SL at LOAS CDFs $CDF_{P,SL,i}(p | [t_{nnn}, t_{mx}])$ determined over all possible times of link failure as indicated in Table 4 for (i) failure pattern *i*, *i* = 1, 2, 3, 4, resulting in LOAS as indicated in Eqs. (4.4)-(4.7) and Table 2, (ii) the system of four links defined and illustrated in Table 1 and Fig. 1 with $[t_{nnn}, t_{mx}] = [0, 200]$, and (iii) quadrature-based evaluation of the integrals in Table 4.

As should be the case, the CDFs in Fig. 8 have structures that are similar to the corresponding CDFs in Fig. 3 for PLOAS.

5.5 Sampling-based Estimation of $CDF_{P,SL,i}(p | [t_{nn}, t_{mx}])$ for System Involving Multiple WLs and SLs. Another possibility is to use a sampling-based procedure to estimate $CDF_{P,SL,i}(p | [t_{nn}, t_{mx}])$. Similarly to the sampling-based procedure to estimate $CDF_{P,LLF}(p | [t_{nn}, t_{mx}])$ and $CDF_{P,FLF}(p | [t_{nn}, t_{mx}])$ described in Sect. 5.3, this procedure involves (i) generating a sample from the defining parameters for the individual links (i.e., the α 's and β 's) in consistency with their specified distributions as defined by the density functions $d_A(\alpha)$ and $d_B(\beta)$ for the individual links and (ii) then determining the resultant failure times and associated failure values. Specifically, a sample

$$\mathbf{p}_{r} = \left[\mathbf{pWL}_{1r}, \mathbf{pWL}_{2r}, \cdots, \mathbf{pWL}_{nWL, r}, \mathbf{pSL}_{1r}, \mathbf{pSL}_{1r}, \cdots, \mathbf{pSL}_{nSL, r}\right], r = 1, 2, \cdots, n$$
(5.28)
ith

$$\mathbf{pWL}_{lr} = \left[\alpha_{WL,lr}, \beta_{WL,lr}\right] \text{ for } l = 1, 2, \cdots, nWL$$
(5.29)

and

W

$$\mathbf{pSL}_{lr} = \left[\alpha_{SL,lr}, \beta_{SL,lr}\right] \text{ for } l = 1, 2, \cdots, nSL$$
(5.30)

is generated from the distributions of the α 's and β 's for the individual links. Next, the link failure times (i.e., tWL_{lr} and tSL_{lr}) and SL failure values (i.e., pSL_{lr}) are determined as functions of elements of the sampled vectors \mathbf{p}_r in Eq. (5.28) as indicated below:

$$tWL_{lr} = tWL_{lr} \left(\mathbf{pWL}_{lr} \right) = tWL_{lr} \left(\alpha_{WL,lr}, \beta_{WL,lr} \right), \tag{5.31}$$

$$tSL_{lr} = tSL_{lr} \left(\mathbf{pSL}_{lr} \right) = tSL_{lr} \left(\alpha_{SL,lr}, \beta_{SL,lr} \right), \tag{5.32}$$

and

$$pSL_{lr} = pSL_{lr}(\mathbf{pSL}_{lr}) = pSL_{lr}(\alpha_{SL,lr}, \beta_{SL,lr}) = \alpha_{SL,lr} \overline{p}_{SL,l}[tSL_{lr}(\alpha_{SL,lr}, \beta_{SL,lr})]$$
(5.33)

with $l = 1, 2, \dots, nWL$ for WLs and $l = 1, 2, \dots, nSL$ for SLs.

Once the results in Eqs. (5.31)-(5.33) are available, the next step is to define the following quantities:

$$\underline{WL}(r) = \text{ link designator for } tWL_{\underline{WL}(r),r} = \min\{tWL_{1r}, tWL_{2r}, \dots, tWL_{nL,r}\},$$
(5.34)

$$\overline{WL}(r) = \text{ link designator for } tWL_{\overline{WL}(r),r} = \max\{tWL_{1r}, tWL_{2r}, \cdots, tWL_{nL,r}\},$$
(5.35)

$$\underline{SL}(r) = \text{ link designator for } tSL_{\underline{SL}(r),r} = \min\{tSL_{1r}, tSL_{2r}, \cdots, tSL_{nL,r}\},$$
(5.36)

$$\overline{SL}(r) = \text{link designator for } tSL_{\overline{SL}(r),r} = \max\{tSL_{1r}, tSL_{2r}, \cdots, tSL_{nL,r}\},$$
(5.37)

and

$$pSL_{\underline{SL}(r),r} = \alpha_{\underline{SL}(r),r} \overline{p}_{\underline{SL}(r)}(tSL_{\underline{SL}(r),r}), pSL_{\overline{SL}(r),r} = \alpha_{\overline{SL}(r),r} \overline{p}_{\overline{SL}(r)}(tSL_{\overline{SL}(r),r}).$$
(5.38)

Further, the indicator function $\delta_{tp}(tWL, tSL, pSL)$ is defined by

$$\delta_{tp}(tWL, tSL, pSL) = \begin{cases} 1 \text{ for } tSL \le \min\{tWL, t_{mx}\} \text{ and } pSL \le p \\ 0 \text{ otherwise,} \end{cases}$$
(5.39)

where (i) p is a WL property value, (ii) tWL is a time at which WL failure potentially prevents LOAS, (iii) tSL is a time at which SL failure potentially results in LOAS, and (iv) pSL is the property value at time tSL of the SL whose failure at time tSL potentially results in LOAS.

Given the results in Eqs. (5.34)-(5.39), $CDF_{P,SL,i}(p | [t_{mn}, t_{mx}])$, i = 1, 2, 3, 4, can be approximated by

$$CDF_{P,SL,1}(p \mid [t_{mn}, t_{mx}]) = \sum_{r=1}^{n} \delta_{tp}(tWL_{\underline{WL}(r), r}, tSL_{\overline{SL}(r), r}, pSL_{\overline{SL}(r), r}) / n,$$
(5.40)

$$CDF_{P,SL,2}(p \mid [t_{mn}, t_{mx}]) = \sum_{r=1}^{n} \delta_{tp}(tWL_{\underline{WL}(r), r}, tSL_{\underline{SL}(r), r}, pSL_{\underline{SL}(r), r}) / n,$$
(5.41)

$$CDF_{P,SL,3}(p | [t_{mn}, t_{mx}]) = \sum_{r=1}^{n} \delta_{tp}(tWL_{\overline{WL}(r),r}, tSL_{\overline{SL}(r),r}, pSL_{\overline{SL}(r),r}) / n$$
(5.42)

and

$$CDF_{P,SL,4}(p \mid [t_{mn}, t_{mx}]) = \sum_{r=1}^{n} \delta_{tp}(tWL_{\overline{WL}(r), r}, tSL_{\underline{SL}(r), r}, pSL_{\underline{SL}(r), r}) / n.$$
(5.43)

5.6 Verification Results for $CDF_{P,SL,i}(p | [t_{mn}, t_{mx}])$. As a verification test, Fig. 9 presents a comparison of CDFs $CDF_{P,SL,i}(p | [t_{mn}, t_{mx}])$, i = 1, 2, 3, 4, for SL property value at LOAS for a system with two WLs and two SLs links obtained by (i) quadrature-based evaluation of the integrals in Table 4 as described in Sect. 5.4 and (ii) a sampling-based calculation as described in Sect. 5.5 and performed with the CPLOAS program [64; 65] and a sample of size $n = 10^6$. The CDFs $CDF_{P,SL,i}(p | [t_{mn}, t_{mx}])$, i = 1, 2, 3, 4, are not defined outputs of the CPLOAS program but (i) these CDFs are calculated as indicated in Sect. 5.5 as part of the SL-SL margin analysis described in Sect. 7.3 and (ii) were obtained for the present analysis by adding a few lines of code to CPLOAS to write them to a saved output file. The results obtained with the two evaluation procedures are essentially identical. This level of agreement provides a strong verification that the two procedures for obtaining $CDF_{P,LLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,FLF}(p | [t_{mn}, t_{mx}])$ are correct in both (i) mathematical development and (ii) computational implementation.

Fig. 9 Verification results for property value of SL at LOAS CDFs $CDF_{P,SL,i}(p | [t_{mn}, t_{mx}])$, i = 1, 2, 3, 4, obtained with quadrature-based procedures (see Sect. 5.4) and sampling-based procedures (see Sect. 5.5) for (i) the four failure patterns resulting in LOAS indicated in Eqs. (4.4)-(4.7) and (ii) the system of four links defined and illustrated in Table 1 and Fig. 1 with $[t_{mn}, t_{mx}] = [0, 200]$.

6. CDFs for Margins Based on WL and SL Property Values

6.1 Formal Representation: CDFs for Margins Based on WL and SL Property Values. For a particular WL/SL configuration (i.e., one of the failure patterns defined in Table 2), let (i) $CDF_{P,WL}(p_{WL} | [t_{mn}, t_{mx}])$ represent the CDF defined on the interval $[pWL_{mn}, pWL_{mx}]$ for the property value p_{WL} at which the failure of the system WLs in the time interval $[t_{mn}, t_{mx}]$ potentially deactivates the system and (ii) $CDF_{P,SL}(p_{SL} | [t_{mn}, t_{mx}])$ represent the CDF defined on the interval $[pSL_{mn}, pSL_{mx}]$ for the property value p_{SL} at which the failure of the system SLs in the time interval $[t_{mn}, t_{mx}]$ potentially results in LOAS. The modifier "potentially" appears in the preceding sentence because the indicated failures may or may not have the indicated effect because of the timing of both WL and SL failures. The CDFs $CDF_{P,WL}(p_{WL} | [t_{mn}, t_{mx}])$ and $CDF_{P,SL}(p_{SL} | [t_{mn}, t_{mx}])$ are defined and illustrated in Sect. 5.1.

The desired CDF $CDF_{PM}(m | [t_{mn}, t_{mx}])$ for property value margin *m* defined by $p_{SL} - p_{WL} = m$ is defined similarly to the time margin CDF $CDF_{TM}(m | [t_{mn}, t_{mx}])$ in Eq. (4.3). Specifically,

$$CDF_{PM}(m | [t_{mn}, t_{mx}]) = prob(p_{SL} - p_{WL} \le m | [t_{mn}, t_{mx}])$$

$$= \lim_{n \to \infty} \sum_{i=1}^{n} CDF_{P,SL}(m + p_i | [t_{mn}, t_{mx}]) \Delta CDF_{P,WL}(p_i | [t_{mn}, t_{mx}])$$

$$= \int_{pWL_{mn}}^{pWL_{mx}} CDF_{P,SL}(m + p | [t_{mn}, t_{mx}]) dCDF_{P,WL}(p | [t_{mn}, t_{mx}])$$

$$= \int_{pWL_{mn}}^{pWL_{mx}} CDF_{P,SL}(m + p | [t_{mn}, t_{mx}]) [dCDF_{P,WL}(p | [t_{mn}, t_{mx}])/dp] dp$$
(6.1)

with p_i , $i = 0, 1, \dots, n$, a subdivision of $[pWL_{mn}, pWL_{mx}]$. However, for this margin to be meaningful, the WLs and SLs must be defined on the basis of the same type of system property and with use of the same units (e.g., temperature in degrees Kelvin).

At this point, the analysis is conceptually the same as the analysis in Sect. 4.3 for failure time margins. However, the challenge is to determine the CDFs $CDF_{P,WL}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,SL}(p | [t_{mn}, t_{mx}])$ in Eq. (6.1). If only one WL (i.e., nWL = 1) and one SL (i.e., nSL = 1) are involved, then the desired CDFs can be determined as indicated in conjunction with Eqs. (3.4) and (3.5). However, the situation is more complex for nWL > 1 and/or nSL > 1. Integral-based and sampling-based procedures to determine $CDF_{P,WL}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,SL}(p | [t_{mn}, t_{mx}])$ for nWL > 1 and nSL > 1 are described in Sects. 5.1 and 5.2. If $CDF_{P,WL,i}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,SL,i}(p | [t_{mn}, t_{mx}])$ can be determined for each of the four failure patterns in Eqs. (4.4)-(4.7) and Table 2, then the corresponding margin CDFs $CDF_{PM,i}(m | [t_{mn}, t_{mx}])$ can be obtained by evaluating the integral

$$CDF_{PM,i}(m | [t_{mn}, t_{mx}]) = \int_{pWL_{mn,i}}^{pWL_{mx,i}} CDF_{P,SL,i}(m + p | [t_{mn}, t_{mx}]) dCDF_{P,WL,i}(p | [t_{mn}, t_{mx}])$$

$$= \int_{pWL_{mn,i}}^{pWL_{mx,i}} CDF_{P,SL,i}(m + p | [t_{mn}, t_{mx}]) \Big[dCDF_{P,WL,i}(p | [t_{mn}, t_{mx}]) / dp \Big] dp,$$
(6.2)

which is the integral in Eq. (6.1) with $CDF_{P,WL,i}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,SL,i}(p | [t_{mn}, t_{mx}])$ replacing $CDF_{P,WL}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,SL}(p | [t_{mn}, t_{mx}])$.

As an example, property margin CDFs $CDF_{PM,i}(m | [t_{mn}, t_{mx}]), i = 1, 2, 3, 4$, for systems with two WLs and two SLs links defined with the WLs and SLs described and illustrated in Table 1 and Fig. 1 are presented in Fig. 10. The associated CDFs $CDF_{P,SL,i}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,WLi}(p | [t_{mn}, t_{mx}])$ in Eq. (6.2) are defined and illustrated in conjunction with Fig. 6. Quadrature-based evaluations of the defining integrals for $CDF_{PM,i}(m | [t_{mn}, t_{mx}])$ in Eq. (6.2) were performed with the MATLAB numerical package [66] as summarized below in a manner similar described in Sect. 4.2 for time margins. to that Specifically, (i) $dCDF_{P,WL,i}(p | [t_{mn}, t_{mx}]) / dt$ was initially approximated with use of the **diff** function and then represented as $ftderCDF_{P,WLi}(p)$ with use of the **fit** function and the 'gauss1' model option, (ii) $CDF_{P,SL,i}(p | [t_{mn}, t_{mx}])$ was represented as $ftCDF_{P,SL,i}(p)$ with use of the fit function and the 'gauss1' model option, and (iii) the integral of $ftCDF_{P,SLi}(p) \times ftderCDF_{P,WLi}(p)$ over $[pWL_{mn,i}, pWL_{mx,i}]$ was evaluated with the **integral** function.

Fig. 10 Weak link (WL)/strong link (SL) property margin CDFs $CDF_{PM,i}(m | [t_{mn}, t_{mx}])$ for (i) failure pattern *i*, *i* = 1, 2, 3, 4, resulting in LOAS as indicated in Table 2, (ii) the system of four links defined and illustrated in Table 1 and Fig. 1 with $[t_{mn}, t_{mx}] = [0, 200]$, and (iii) quadrature-based evaluation of the integrals in Eq. (6.2).

6.2 Sampling-based Estimation of $CDF_{MP}(m|[t_{mn},t_{mx}])$ Based on WL and SL Property Values. The CDFs $CDF_{P,WL,i}(p|[t_{mn},t_{mx}])$ and $CDF_{P,SL,i}(p|[t_{mn},t_{mx}])$ can also be used in a sampling-based procedure to estimate $CDF_{PM,i}(m|[t_{mn},t_{mx}])$ that is analogous to the samplingbased procedure in Eq. (4.17) to estimate $CDF_{TM,i}(m|[t_{mn},t_{mx}])$. Specifically,

$$prob_{i}\left(p_{SL} - p_{WL} \le m \,|\, [t_{mn}, t_{mx}]\right) \cong \sum_{r=1}^{n} \delta_{m}\left(p_{SL,r} - p_{WL,r}\right) / n \tag{6.3}$$

for (i) a random sample $[p_{SL,r}, p_{WL,r}]$, r = 1,2, ..., n, from $[pSL_{mn,i}, pSL_{mx,i}] \times [pWL_{mn,i}, pWL_{mx,i}]$ obtained with use of $CDF_{P,SL,i}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,WL,i}(p | [t_{mn}, t_{mx}])$, and (ii) $\delta_m(\Box)$ defined as in Eq. (4.16).

However, given the complexity of $CDF_{P,WL,i}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,SL,i}(p | [t_{mn}, t_{mx}])$, their direct use in the determination of the distribution for the margin *m* defined by $p_{SL} - p_{WL}$ may not be computationally convenient. Instead, a procedure based on sampling the defining parameters for the individual links (i.e., the α 's and β 's) and then determining the resultant margins may be more practicable. Specifically, a sampling-based procedure similar to the procedure described in conjunction with Eqs. (4.21)-(4.25) to determine $prob_i(t_{SL} - t_{WL} \le m)$ can also be used to determine $prob_i(p_{SL} - p_{WL} \le m | [t_{mn}, t_{mx}])$ for the margin *m* defined by

 $p_{SL} - p_{WL}$ with *i* indicating Patterns 1-4 described in Eqs. (4.4)-(4.7) and correspondingly the four WL/SL failure patterns in Table 2.

The indicated procedure to determine $prob_i(p_{SL} - p_{WL} \le m | [t_{mn}, t_{mx}])$ begins with (i) a sample $\mathbf{s}_r, r = 1, 2, \dots, n$ of the form indicated in Eqs. (4.21)-(4.23), (ii) the associated link failure times

$$tWL_{lr}, l = 1, 2, \cdots, nWL, \text{ and } tSL_{lr}, l = 1, 2, \cdots, nSL,$$
 (6.4)

defined in Eqs. (4.24)-(4.25), and (iii) the resultant link system failure times

$$\overline{tSL}_{k(r),r}, \underline{tSL}_{k(r),r}, \overline{tWL}_{l(r),r}, \underline{tWL}_{l(r),r}$$
(6.5)

defined in Eq. (4.19). Once the link system failure times are available, the desired property margins are given by

$$m_{i}\left(\mathbf{S}_{r}\right) = \begin{cases} \alpha_{SL,k(r),r} \,\overline{p}_{SL,k(r)}\left(\overline{tSL}_{k(r),r}\right) - \alpha_{WL,l(r),r} \,\overline{p}_{WL,l(r)}\left(\underline{tWL}_{l(r),r}\right) & \text{for } i = 1\\ \alpha_{SL,k(r),r} \,\overline{p}_{SL,k(r)}\left(\underline{tSL}_{k(r),r}\right) - \alpha_{WL,l(r),r} \,\overline{p}_{WL,l(r)}\left(\underline{tWL}_{l(r),r}\right) & \text{for } i = 2\\ \alpha_{SL,k(r),r} \,\overline{p}_{SL,k(r)}\left(\overline{tSL}_{k(r),r}\right) - \alpha_{WL,l(r),r} \,\overline{p}_{WL,l(r)}\left(\overline{tWL}_{l(r),r}\right) & \text{for } i = 3\\ \alpha_{SL,k(r),r} \,\overline{p}_{SL,k(r)}\left(\underline{tSL}_{k(r),r}\right) - \alpha_{WL,l(r),r} \,\overline{p}_{WL,l(r)}\left(\overline{tWL}_{l(r),r}\right) & \text{for } i = 4 \end{cases}$$
(6.6)

and the resultant approximation to $prob_i(p_{SL} - p_{WL} \le m | [t_{mn}, t_{mx}])$ is obtained as in Eq. (4.20) for $prob_i(t_{SL} - t_{WL} \le m)$.

6.3 Verification Results for $CDF_{PM,i}(p | [t_{mn}, t_{mx}])$. As a verification test, Fig. 11 presents a comparison of CDFs $CDF_{PM,i}(p | [t_{mn}, t_{mx}])$, i = 1, 2, 3, 4, for property value margins for a system with two WLs and two SLs obtained by (i) quadrature-based evaluation of the integrals in Eq. (6.2) as described in Sect. 6.1 and (ii) a sampling-based calculation as described in Sect. 6.2 and performed with the CPLOAS program [64; 65] and a sample of size $n = 10^6$. The CDFs $CDF_{PM,i}(p | [t_{mn}, t_{mx}])$, i = 1, 2, 3, 4, are not defined outputs of the CPLOAS program but (i) these CDFs are calculated as indicated in Sect. 6.2 as part of the SL-SL margin analysis described in Sect. 7.3 and (ii) were obtained for the present analysis by adding a few lines of code to CPLOAS to write them to a saved output file. The results obtained with the two evaluation procedures are essentially identical. This level of agreement provides a strong verification that the two procedures for obtaining $CDF_{PM,i}(p | [t_{mn}, t_{mx}])$ are correct in both (i) mathematical development and (ii) computational implementation.

Fig. 11 Verification results for WL/SL property value margin CDFs $CDF_{PM,i}(p | [t_{mn}, t_{mx}]), i = 1, 2, 3, 4$, obtained with quadrature-based procedures (see Sect. 6.1) and sampling-based

procedures (see Sect. 6.2) for (i) the four failure patterns resulting in LOAS indicated in Table 2 and (ii) the system of four links defined and illustrated in Table 1 and Fig. 1 with $[t_{mn}, t_{mx}] = [0, 200]$.

7. CDFs for Margins Involving Only SL Property Values

7.1 Preliminaries: CDFs for Margins Involving Only SL Property Values. Margins involving only SL property values for a WL/SL configuration involving *nWL* WLs and *nSL* SLs are now considered. For the situation in which WL failures potentially deactivate the system at time t_{WL} and SL failures potentially result in LOAS at time t_{SL} , the margin of interest is defined to be the difference

$$p_{k}(t_{SL} \mid \alpha) - p_{k}(t_{WL} \mid \alpha) = \alpha \overline{p}_{k}(t_{SL}) - \alpha \overline{p}_{k}(t_{WL}) = m_{k}(\alpha, t_{SL}, t_{WL})$$
(7.1)

between the property value $p_k(t_{SL} | \alpha) = \alpha \overline{p}_k(t_{SL})$ of the SL (i.e., SL k) whose time of failure corresponds to t_{SL} and the property value $p_k(t_{WL} | \alpha) = \alpha \overline{p}_k(t_{WL})$ of this same SL at the time that the WL failure potentially deactivates the system (i.e., t_{WL}). The following entities are used in the derivation of the CDF $CDF_{PM,SL}(m | [t_{mn}, t_{mx}])$ for the SL property value margin m defined in Eq. (7.1) for link failures in the time interval $[t_{mn}, t_{mx}]$:

$$CDF_{T,WL}(t) = CDF$$
 defined on $[t_{mn}, t_{mx}]$ for time at which WL failure potentially
averts LOAS (i.e., at last WL failure or first WL failure as defined (7.2)
in Eqs. (4.1) and (4.2)),

$$CDF_{T,SL,k}(t) = \text{CDF}$$
 defined on $[t_{mn}, t_{mx}]$ for time at which SL k fails with
corresponding density function $d_{T,SL,k}(t)$, (7.3)

and

 $CDF_{Ak}(\alpha | t_F) = CDF$ for α values for SL k that could result in failure of SL k at time t_F conditional on SL k having failed at time t_F with corresponding (7.4) density function $d_{Ak}(\alpha | t_F)$.

The CDF $CDF_{T,WL}(t)$ is defined in Eq. (4.1) or (4.2) as appropriate. A derivation for $CDF_{Ak}(\alpha | t_F)$ is presented in Sect. 9.4 of Ref. [8], and the resultant values for $CDF_{Ak}(\alpha | t_F)$ and $d_{Ak}(\alpha | t_F)$ are summarized in Table 5 of Ref. [8]. Further, the ranges of α values associated with $CDF_{Ak}(\alpha | t_F)$ and $d_{Ak}(\alpha | t_F)$ are summarized in Tables 4 and 5 of Ref. [8] and reproduced in this presentation as Table 5.

Table 5 Intervals $[\alpha_{mn}(\tau), \alpha_{mx}(\tau)]$ of values for α resulting in link failure conditional on link failure at time τ with $\overline{p}(\tau)$ increasing and $\overline{q}(\tau)$ either decreasing or constant-valued (adapted from Ref. [8], Tables 4 and 5).

7.2 Formal Representation: CDFs for Margins Involving Only SL Property Values. The integral representations for $CDF_{PM,SL}(m | [t_{mn}, t_{mx}])$ are complex. As a result of α, t_{SL} and t_{WL} each having a distribution, the integral representations for $CDF_{PM,SL}(m | [t_{mn}, t_{mx}])$ will involve triple integrals. As indicated in Table 2, definition of LOAS involves two possible definitions of WL system failure and two possible definitions of SL system failure, with the two possible definitions for each type of link corresponding to (i) time of first link failure and (ii) time of last link failure. In the following, the two possible definitions of WL failure are assumed to have been appropriately incorporated into the definition of $CDF_{T,WL}(t)$ as indicated in Eqs. (4.1) and (4.2). The effects of the two link failure definitions for SLs are introduced into the representations for $CDF_{PM,SL}(m | [t_{mn}, t_{mx}])$ through the notation

$$P_{k}(\tau) = \prod_{l=1, l \neq k}^{nSL} \left[1 - CDF_{T,SL,l}(\tau) \right]$$
for LOAS associated with first SL failure (7.5)

and

$$P_k(\tau) = \prod_{l=1, l \neq k}^{nSL} CDF_{T,SL,l}(\tau) \text{ for LOAS associated with last SL failure.}$$
(7.6)

In addition, (i) possible values m < 0, m = 0, and 0 < m are considered for *m* in the definition of $CDF_{PM,SL}(m | [t_{mn}, t_{mx}])$, (ii) the notation

$$d_k(\tau,t) = \overline{p}_k(\tau) - \overline{p}_k(t)$$
(7.7)

is used to simplify some of the following expressions, and (iii) a subdivision t_i , $i = 0, 1, \dots, n$, of the time interval $[t_{mn}, t_{mn}]$ with

$$t_{\underline{n}(k)} = \text{ first time at which SL } k \text{ fails}$$

$$= r_k^{-1} (\alpha_{mx} / \beta_{mn})$$

$$= \tau_{fk}$$
(7.8)

 $t_{\overline{n}(k)} =$ last time at which SL k fails

$$=\begin{cases} r_k^{-1}(\alpha_{mn} / \beta_{mx}) & \text{if SL } k \text{ always fails in time interval } [t_{mn}, t_{mx}] \\ t_{mx} & \text{if SL } k \text{ may not fail in time interval } [t_{mn}, t_{mx}] \\ = \tau_{lk} \end{cases}$$
(7.9)

is under consideration.

For m < 0, $CDF_{PM,SL}(m | [t_{mn}, t_{mx}])$ can be approximated by

$$CDF_{PM,SL}(m | [t_{mn}, t_{mx}] \text{ with } m < 0)$$

$$= \lim_{n \to \infty} \sum_{k=1}^{nSL} \sum_{i=\underline{n}(k)+2}^{n} \sum_{j=\underline{n}(k)+1}^{\min\{i-1,\overline{n}(k)\}} \left[prob_{Ak} \left(\alpha : \alpha \overline{p}_{k}(t_{j}) - \alpha \overline{p}_{k}(t_{i}) \le m \right) \right]$$

$$\times \left[P_{k}(t_{j}) \times \Delta CDF_{T,SL,k}(t_{j}) \right] \Delta CDF_{T,WL}(t_{i}) \qquad (7.10)$$

$$= \lim_{n \to \infty} \sum_{k=1}^{nSL} \sum_{i=\underline{n}(k)+2}^{n} \sum_{j=\underline{n}(k)+1}^{\min\{i-1,\overline{n}(k)\}} \left[prob_{Ak} \left(\alpha : \alpha \overline{p}_{k}(t_{j}) - \alpha \overline{p}_{k}(t_{i}) \le m \right) \right]$$

$$\times \left[P_{k}(t_{j}) \times d_{T,SL,k}(t_{j}) \Delta t_{j} \right] \Delta CDF_{T,WL}(t_{i}),$$

with

$$prob_{Ak} \left(\alpha : \alpha \,\overline{p}_k(t_j) - \alpha \,\overline{p}_k(t_i) \le m \right) = \text{probability of a negative SL time margin } \le m$$

conditional on (i) failure of SL k at time t_j resulting in LOAS and (ii) failure of
the WL system at time $t_i > t_j$. (7.11)

$$\Delta CDF_{T,SL,k}(t_j) = \text{ probability that SL } k \text{ fails in time interval } \Delta t_j, \qquad (7.12)$$

$$P_{k}(t_{j}) \times \Delta CDF_{t,SL,k}(t_{j}) \cong P_{k}(t_{j}) \times d_{T,SL,k}(t_{j}) \Delta t_{j}$$

$$\cong \text{ probability that failure of SL } k \text{ in time interval } \Delta t_{j}$$
(7.13)
could result in LOAS,

$$\Delta CDF_{T,WL}(t_i) = \text{ probability that WL system fails in time interval } \Delta t_i, \qquad (7.14)$$

and the indicated offsets involving *i* and *j* defined to produce negative margins and also to avoid the potential for a later division by zero. Part of the preceding approximation to $CDF_{PM,SL}(m | [t_{nn}, t_{mx}] \text{ with } m < 0)$ can be simplified as follows:

$$prob_{Ak} \left(\alpha : \alpha \,\overline{p}_{k}(t_{j}) - \alpha \,\overline{p}_{k}(t_{i}) \leq m \right) d_{T,SL,k}(t_{j})$$

$$= prob_{Ak} \left(\alpha : \alpha d_{k}(t_{j},t_{i}) \leq m \right) d_{T,SL,k}(t_{j})$$

$$= prob_{Ak} \left(\alpha : m / d_{k}(t_{j},t_{i}) \leq \alpha \right) d_{T,SL,k}(t_{j})$$

$$= CCDF_{Ak} \left(m / d_{k}(t_{j},t_{i}) \mid t_{j} \right) d_{T,SL,k}(t_{j})$$

$$= \int_{m/d_{k}(t_{j},t_{i})}^{\alpha_{mx,k}(t_{j})} d_{Ak} \left(\alpha \mid t_{j} \right) d_{T,SL,k}(t_{j}) d\alpha$$

$$= \left[d \left[\overline{p}_{k}(\tau) / \overline{q}_{k}(\tau) \right] / d\tau \right]_{\tau=t_{j}} \left[\int_{\alpha_{mn,k}(t_{j},t_{i})}^{\alpha_{mn,k}(t_{j},t_{i})} \alpha d_{Ak}(\alpha) d_{Bk} \left(\alpha / r_{k}(t_{j}) \right) d\alpha \right],$$
(7.15)

where (i) the equality

$$d_{Ak}(\alpha \mid t_j)d_{T,SL,k}(t_j) = \left[d\left[\overline{p}_k(\tau)/\overline{q}_k(\tau)\right]/d\tau\right]_{\tau=t_j} \alpha d_{Ak}(\alpha)d_{Bk}\left(\alpha/r_k(t_j)\right)$$
(7.16)

is derived in Sect. 9.6 of Ref. [8], (ii)

$$\alpha_{mn,k}(t_j, t_i) = \max\left\{\alpha_{mn,k}(t_j), m / d_k(t_j, t_i)\right\} \text{ and } \alpha_{mx,k}(t_j)$$
(7.17)

together define the intervals over which the associated integral is nonzero provided the inequality

$$m / d_k(t_j, t_i) < \alpha_{mx,k}(t_j)$$
(7.18)

is valid, and (iii) the interval $[\alpha_{mn,k}(t_j), \alpha_{mx,k}(t_j)]$ for each SL is defined in Table 5. Additional details on the definitions of the intervals $[\alpha_{mn,k}(\tau,t), \alpha_{mx,k}(\tau)]$ are given in Eqs. (7.21) and (7.22).

In turn, substitution of the result in Eq. (7.15) into the representation for $CDF_{PM}(m | [t_{mn}, t_{mx}] \text{ with } m < 0)$ in Eq. (7.10) produces the result

$$CDF_{PM,SL}(m | [t_{mn}, t_{mx}] \text{ with } m < 0)$$

$$= \lim_{n \to \infty} \sum_{k=1}^{nSL} \sum_{i=\underline{n}(k)+2}^{n} \sum_{j=\underline{n}(k)+1}^{\min\{i-1,\overline{n}(k)\}} P_k(t_j) \Big[d\big[\overline{p}_k(\tau)/\overline{q}_k(\tau)\big]/d\tau \Big]_{\tau=t_j}$$

$$\times \Big[\int_{\alpha_{mn,k}(t_j,t_i)}^{\alpha_{mn,k}(t_j)} \alpha d_{Ak}(\alpha) d_{Bk} (\alpha/r_k(t_j)) d\alpha \Big] \Delta \tau_j \Delta CDF_{T,WL}(t_i)$$

$$= \sum_{k=1}^{nSL} \int_{\tau_{jk}}^{t_{mx}} \Big\{ \int_{\tau_{jk}}^{\min\{t,\tau_{lk}\}} \Big(P_k(\tau) \Big[d\big[\overline{p}_k(\tau)/\overline{q}_k(\tau)\big]/d\tau \Big] \\ \times \Big[\int_{\alpha_{mn,k}(\tau,\tau)}^{\alpha_{mx,k}(\tau)} \alpha d_{Ak}(\alpha) d_{Bk} (\alpha/r_k(\tau)) d\alpha \Big] \Big] d\tau \Big] dCDF_{T,WL}(t)$$

$$= \sum_{k=1}^{nSL} \int_{\tau_{jk}}^{t_{mx}} \int_{\tau_{jk}}^{\min\{t,\tau_{lk}\}} \int_{\alpha_{mn,k}(\tau,\tau)}^{\alpha_{mx,k}(\tau)} f_k(\alpha,\tau,t) d\alpha d\tau dt$$

$$(7.19)$$

with

$$f_{k}(\alpha,\tau,t) = \left[\alpha d_{Ak}(\alpha) d_{Bk}(\alpha/r_{k}(\tau))\right] P_{k}(\tau) \left[d\left[\overline{p}_{k}(\tau)/\overline{q}_{k}(\tau)\right]/d\tau\right] \left[dCDF_{T,WL}(t)/dt\right]$$
(7.20)

and the second equality resulting in the limit as $n \rightarrow \infty$.

With use of the definitions of the intervals $[\alpha_{mn}(\tau), \alpha_{mx}(\tau)]$ in Table 5, it follows that the integration limits for the inner integral over α in Eq. (7.19) are given by

$$\left[\alpha_{mn,k}(\tau,t),\alpha_{mx,k}(\tau)\right] = \begin{cases} \left[\max\{\beta_{mn,k}r_{k}(\tau), m / d_{k}(\tau,t)\}, \alpha_{mx,k}\right] & \text{for } \tau \in \mathcal{P}_{1} \\ \left[\max\{\beta_{mn,k}r_{k}(\tau), m / d_{k}(\tau,t)\}, \beta_{mx,k}r_{k}(\tau)\right] & \text{for } \tau \in \mathcal{P}_{2} \\ \left[\max\{\alpha_{mn,k}, m / d_{k}(\tau,t)\}, \alpha_{mx,k}\right] & \text{for } \tau \in \mathcal{P}_{3} \\ \left[\max\{\alpha_{mn,k}, m / d_{k}(\tau,t)\}, \beta_{mx,k}r_{k}(\tau)\right] & \text{for } \tau \in \mathcal{P}_{4} \end{cases}$$
(7.21)

with the definitions of the sets \mathcal{P}_i , i = 1, 2, 3, 4, conditional on the relationships

$$\alpha_{mn} / \beta_{mn} < \alpha_{mx} / \beta_{mx}, \ \alpha_{mx} / \beta_{mx} < \alpha_{mn} / \beta_{mn} \text{ and } \alpha_{mn} / \beta_{mn} = \alpha_{mx} / \beta_{mx}.$$
(7.22)

The sets \mathcal{P}_i , i = 1, 2, 3, 4, and their connections to the relationships in Eq. (7.22) are defined in Table 5. Further, for

$$\alpha_{mx,k}(\tau) \le m / d_k(\tau, t), \tag{7.23}$$

the integral over α in Eq. (7.19) is equal to 0.

Because the SL property value functions $\overline{p}_k(\tau)$ are increasing, a SL temperature margin $m \le 0$ can only occur if failure of the SL system occurs before or at the same time as failure of the WL system. As a result, $CDF_{PM,SL}(0 | [t_{mn}, t_{mx}])$ is defined by

$$CDF_{PM,SL}(0 | [t_{mn}, t_{mx}]) = \lim_{n \to \infty} \sum_{k=1}^{nSL} \sum_{i=\underline{n}(k)+2}^{n} \sum_{j=\underline{n}(k)+1}^{\min\{i-1,\overline{n}(k)\}} \left[P_{k}(t_{j}) \times \Delta CDF_{T,SL,k}(t_{j}) \right] \Delta CDF_{T,WL}(t_{i})$$

$$= \sum_{k=1}^{nSL} \int_{\tau_{fk}}^{t_{mx}} \left[\int_{\tau_{fk}}^{\min\{t,\tau_{lk}\}} P_{k}(\tau) dCDF_{T,SL,k}(\tau) \right] dCDF_{T,WL}(t)$$

$$= \sum_{k=1}^{nSL} \int_{\tau_{fk}}^{t_{mx}} \int_{\tau_{fk}}^{\min\{t,\tau_{lk}\}} g_{k}(\tau, t) d\tau dt$$
(7.24)

with (i) the second equality resulting in the limit as $n \rightarrow \infty$ and (ii)

$$g_{k}(\tau,t) = P_{k}(\tau) \left[dCDF_{T,SL,k}(\tau) / d\tau \right] \left[dCDF_{T,WL}(t) / dt \right]$$
(7.25)

in the third equality. The preceding representation for $CDF_{PM,SL}(0 | [t_{mn}, t_{mx}])$ is the same as the representation for $CDF_{PM,SL}(m | [t_{mn}, t_{mx}])$ with m < 0 in Eq. (7.10) with $prob_{Ak}(\cdots)$ replaced by 1.0.

For m > 0, $CDF_{PM,SL}(m | [t_{mn}, t_{mx}])$ can be approximated by

$$CDF_{PM,SL}(m | [t_{mn}, t_{mx}] \text{ with } 0 < m)$$

$$= CDF_{PM}(0 | [t_{mn}, t_{mx}]) + \lim_{n \to \infty} \sum_{k=1}^{nSL} \sum_{i=1}^{\overline{n}(k)} \sum_{j=\max\{i+1,\underline{n}(k)\}}^{\overline{n}(k)} \left[prob_{Ak} \left(\alpha : \alpha \overline{p}_{k}(t_{j}) - \alpha \overline{p}_{k}(t_{i}) \le m \right) \right]$$

$$\times \left[P_{k}(t_{j}) \times \Delta CDF_{T,SL,k}(t_{j}) \right] \Delta CDF_{T,WL}(t_{i})$$

$$= CDF_{PM}(0 | [t_{mn}, t_{mx}]) + \lim_{n \to \infty} \sum_{k=1}^{nSL} \sum_{i=1}^{\overline{n}(k)-1} \sum_{j=\max\{i+1,\underline{n}(k)\}}^{\overline{n}(k)} \left[prob_{Ak} \left(\alpha : \alpha \overline{p}_{k}(t_{j}) - \alpha \overline{p}_{k}(t_{i}) \le m \right) \right]$$

$$\times \left[P_{k}(t_{j}) \times d_{T,SL,k}(t_{j}) \Delta t_{j} \right] \Delta CDF_{T,WL}(t_{i})$$

$$(7.26)$$

with (i)

 $prob_{Ak} \left(\alpha : \alpha \,\overline{p}_k(t_j) - \alpha \,\overline{p}_k(t_i) \le m \right) = \text{probability of a positive SL time margin}$ $\le m \text{ conditional on (a) failure of SL } k \text{ at time } t_j \text{ corresponding to LOAS and}$ (b) failure of the WL system at time $t_i < t_j$, (7.27) (ii) $\Delta CDF_{T,SL,k}(t_j)$, $P_k(t_j) \times \Delta CDF_{T,SL,k}(t_j)$, $P_k(t_j) \times d_{T,SL,k}(t_j)\Delta t_j$ and $\Delta CDF_{T,WL}(t_i)$ defined in Eqs. (7.12)-(7.14), and (iii) the indicated offsets involving *i* and *j* defined to produce positive margins and also to avoid the potential for a later division by zero. Similarly to the development in Eq.(7.15), part of the preceding approximation to $CDF_{PM}(m | 0 < m)$ can be simplified as follows:

$$prob_{Ak} \left(\alpha : \alpha \,\overline{p}_{k}(t_{j}) - \alpha \,\overline{p}_{k}(t_{i}) \leq m \right) d_{Tk}(t_{j})$$

$$= prob_{Ak} \left(\alpha : \alpha d_{k}(t_{j},t_{i}) \leq m \right) d_{Tk}(t_{j})$$

$$= prob_{Ak} \left(\alpha : \alpha \leq m / d_{k}(t_{j},t_{i}) \right) d_{Tk}(t_{j})$$

$$= CDF_{Ak} \left(m / d_{k}(t_{j},t_{i}) \mid t_{j} \right) d_{Tk}(t_{j})$$

$$= \int_{\alpha_{mn,k}(t_{j})}^{m/d_{k}(t_{j},t_{i})} d_{Ak}(\alpha \mid t_{j}) d_{Tk}(t_{j}) d\alpha$$

$$= \left[d \left[\overline{p}_{k}(\tau) / \overline{q}_{k}(\tau) \right] / d\tau \right]_{\tau=t_{j}} \left[\int_{\alpha_{mn,k}(t_{j})}^{\alpha_{mn,k}(t_{j},t_{i})} \alpha d_{Ak}(\alpha) d_{Bk}(\alpha / r_{k}(t_{j})) d\alpha \right],$$
(7.28)

where (i) the substitution for $d_{Ak}(\alpha | t_j) d_{Tk}(t_j)$ is defined in Eq. (7.16), (ii)

$$\alpha_{mn,k}(t_j) \text{ and } \alpha_{mx,k}(t_j,t_i) = \min\left\{\alpha_{mx,k}(t_j), m/d_k(t_j,t_i)\right\}$$
(7.29)

together define the intervals over which the associated integral is nonzero provided the inequality

$$\alpha_{mn,k}(t_j) < m / d_k(t_j, t_i) \tag{7.30}$$

is valid, and (iii) the interval $[\alpha_{mn,k}(t_j), \alpha_{mx,k}(t_j)]$ for each SL is defined in Table 5. Additional details on the definitions of the intervals $[\alpha_{mn,k}(\tau,t), \alpha_{mx,k}(\tau)]$ are given in Eqs. (7.32) and (7.22).

In turn, substitution of the result in Eq. (7.28) into the representation for $CDF_{PM,SL}(m | [t_{mn}, t_{mx}] \text{ with } m < 0)$ in Eq. (7.26) produces the result

 $CDF_{PM,SL}(m | [t_{mn}, t_{mx}] \text{ with } 0 < m)$

$$= CDF_{PM,SL}(0 | [t_{mn}, t_{mx}]) + \lim_{n \to \infty} \sum_{k=1}^{nSL} \sum_{i=1}^{\overline{n}(k)} \sum_{j=\max\{i+1,\underline{n}(k)\}}^{\overline{n}(k)} P_k(t_j) \Big[d\big[\overline{p}_k(\tau) / \overline{q}_k(\tau) \big] / d\tau \Big]_{\tau=t_j} \\ \times \Big[\int_{\alpha_{mn,k}(t_j)}^{\alpha_{mn,k}(t_j)} \alpha d_{Ak}(\alpha) d_{Bk} \left(\alpha / r_k(t_j) \right) d\alpha \Big] \Delta t_j \Delta CDF_{T,WL}(t_i) \\ = CDF_{PM,SL}(0 | [t_{mn}, t_{mx}]) + \sum_{k=1}^{nSL} \int_{t_{mn}}^{\tau_{lk}} \Big\{ \int_{\max\{t,\tau_{fk}\}}^{\tau_{lk}} \Big(P_k(\tau) \Big[d\big[\overline{p}_k(\tau) / \overline{q}_k(\tau) \big] / d\tau \Big] \\ \times \Big[\int_{\alpha_{mn,k}(\tau)}^{\alpha_{mx,k}(\tau,t)} \alpha d_{Ak}(\alpha) d_{Bk} \left(\alpha / r_k(\tau) \right) d\alpha \Big] \Big] d\tau \Big] dCDF_{T,WL}(t)$$

$$= CDF_{PM,SL}(0 | [t_{mn}, t_{mx}]) + \sum_{k=1}^{nSL} \int_{t_{mn}}^{\tau_{lk}} \int_{\max\{t,\tau_{fk}\}}^{\alpha_{mx,k}(\tau,t)} f_k(\alpha, \tau, t) d\alpha d\tau dt$$

$$(7.31)$$

with the second equality resulting in the limit as $n \to \infty$ and $f_k(\alpha, \tau, t)$ defined the same as in Eq. (7.20).

With use of the definitions of the intervals $[\alpha_{mn}(\tau), \alpha_{mx}(\tau)]$ in Table 5, it follows that the integration limits for the inner integral over α in Eq. (7.31) are given by

$$\left[\alpha_{mn,k}(\tau), \alpha_{mx,k}(\tau,t)\right] = \begin{cases} \left[\beta_{mn,k}r_{k}(\tau), \min\{\alpha_{mx,k}, m/d_{k}(\tau,t)\}\right] & \text{for } \tau \in \mathcal{P}_{1} \\ \left[\beta_{mn,k}r_{k}(\tau), \min\{\beta_{mx,k}r_{k}(\tau, m/d_{k}(\tau,t)\}\right] & \text{for } \tau \in \mathcal{P}_{2} \\ \left[\alpha_{mn,k}, \min\{\alpha_{mx,k}, m/d_{k}(\tau,t)\}\right] & \text{for } \tau \in \mathcal{P}_{3} \\ \left[\alpha_{mn,k}, \min\{\beta_{mx,k}r_{k}(\tau), m/d_{k}(\tau,t)\}\right] & \text{for } \tau \in \mathcal{P}_{4} \end{cases}$$
(7.32)

with the definitions of the sets \mathcal{P}_i , i = 1, 2, 3, 4, conditional on the relationships in Eq. (7.22). Further, for

$$m/d_k(\tau,t) \le \alpha_{mx,k}(\tau), \tag{7.33}$$

the integral over α in Eq. (7.31) is equal to 0.

As a reminder, the preceding derivations for

$$CDF_{PM,SL}(m | [t_{mn}, t_{mx}]) = \begin{cases} CDF_{PM,SL}(m | [t_{mn}, t_{mx}] \text{ with } m < 0) \\ CDF_{PM,SL}(0 | [t_{mn}, t_{mx}]) \\ CDF_{PM,SL}(m | [t_{mn}, t_{mx}] \text{ with } 0 < m) \end{cases}$$
(7.34)

define $CDF_{PM,SL}(m | [t_{mn}, t_{mx}])$ for the four failure patterns corresponding to the definition of $pF_i(t), i = 1, 2, 3, 4$, in Table 2. The four definitions for $CDF_{PM,SL}(m | [t_{mn}, t_{mx}])$ denoted by $CDF_{PM,SL,i}(m | [t_{mn}, t_{mx}]), i = 1, 2, 3, 4$, are determined by the definitions used in Eqs. (7.19) and (7.31) for $CDF_{T,WL}(t)$ (see Eq. (7.2)) and $P_k(t)$ (see Eqs. (7.5) and (7.6)). Specifically,

$$CDF_{PM,SL,1}(m | [t_{mn}, t_{mx}]) \sim \text{Failure Pattern 1 in Table 2 with } CDF_{T,WL}(t) \text{ and } P_k(k)$$

defined in Eqs. (4.2) and (7.6), (7.35)

$$CDF_{PM,SL,2}(m | [t_{mn}, t_{mx}]) \sim \text{Failure Pattern 2 in Table 2 with } CDF_{T,WL}(t) \text{ and } P_k(k)$$

defined in Eqs. (4.2) and (7.5), (7.36)

$$CDF_{PM,SL,3}(m | [t_{mn}, t_{mx}]) \sim \text{Failure Pattern 3 in Table 2 with } CDF_{T,WL}(t) \text{ and } P_k(k)$$

defined in Eqs. (4.1) and (7.6), (7.37)

and

$$CDF_{PM,SL,4}(m | [t_{mn}, t_{mx}]) \sim \text{Failure Pattern 4 in Table 2 with } CDF_{T,WL}(t) \text{ and } P_k(k)$$
defined in Eqs. (4.1) and (7.5).
$$(7.38)$$

As an example, SL property margin CDFs $CDF_{PM,SL,i}(m | [t_{mn}, t_{mx}]), i = 1, 2, 3, 4,$ for systems with two WLs and two SLs links defined with the WLs and SLs described and illustrated in Table 1 and Fig. 1 are presented in Fig. 12. Quadrature-based evaluations of the defining triple integrals for $CDF_{PM,SLi}(m | [t_{mn}, t_{mx}])$ in Eqs. (7.19) and (7.31) were performed with procedures contained in the MATLAB numerical analysis package [66]. Both integrals have the function $f_k(\alpha, \tau, t)$ defined in Eq. (7.20) as an integrand, the components of which were evaluated as follows: (i) the density functions $d_{Ak}(\alpha)$ and $d_{Bk}(\beta)$ were defined with the makedist, fitdist and pdf functions, (ii) the failure time CDFs associated with the products in $P_k(\tau)$ were defined with the spline and ppval functions, (iii) the derivative $d\left[\bar{p}_{k}(\tau)/\bar{q}_{k}(\tau)\right]/d\tau$ was defined with use of the **diff** and **matlabFunction** functions, and (iv) the derivative $dCDF_{T,WL}(t)/dt$ was obtained by first constructing a spline representation for $CDF_{WL}(t)$ with the spline function and then differentiating this representation with the fnder function. The limits of integration were defined with the min and max functions. The overall calculation was performed for each margin value m by (i) discretizing the time domain into 150 evenly spaced times and (ii) calculating the inner two integrals at each time with the TwoD program [68]. This defined a function over time that was approximated with the spline function and then integrated with the integral function to obtain the value for the triple integral. The process was repeated for multiple values of m to obtain the SL property margin CDFs $CDF_{PM,SL,i}(m | [t_{mn}, t_{mx}]), i = 1, 2, 3, 4, in Fig. 12$. The approximation of the double integral in Eq. (7.24) defining $CDF_{PM,SL}(0 | [t_{mn}, t_{mx}])$, i = 1, 2, 3, 4, for the four failure patterns can be performed with the **TwoD** program and appropriate representations for the three functions whose product defines the associated integrand $g_k(\tau,t)$ defined in Eq. (7.25).

Fig. 12 Strong link (SL) property margin CDFs $CDF_{PM,SL,i}(m | [t_{mn}, t_{mx}])$ for (i) failure pattern *i*, i = 1, 2, 3, 4, resulting in LOAS as indicated in Table 2, (ii) the system of four links defined and illustrated in Table 1 and Fig. 1 with $[t_{mn}, t_{mx}] = [0, 200]$, and (iii) quadrature-based evaluation of the integrals in Eqs. (7.19), (7.24) and (7.31).

7.3 Sampling-based Estimation of CDFs $CDF_{PM,SL,i}(m | [t_{mn},t_{mx}])$ for Margins Involving Only SL Property Values. Given the complexity of the integrals in Eqs. (7.19) and (7.31), it is likely to be more practicable to estimate $CDF_{PM,SL,i}(m | [t_{mn},t_{mx}])$ by a sampling-based procedure than by numerical evaluation of these integrals. Specifically, the same procedure described in conjunction with Eqs. (6.4)-(6.6) can be used to estimate $CDF_{PM,SL,i}(m | [t_{mn},t_{mx}])$ with the only difference being a change in the definition of $m_i(\mathbf{s}_r)$ in Eq. (6.6) to

$$m_{i}\left(\mathbf{S}_{r}\right) = \begin{cases} \alpha_{SL,k(r),r}\,\overline{p}_{SL,k(r)}\left(\overline{tSL}_{k(r),r}\right) - \alpha_{SL,k(r),r}\,\overline{p}_{SL,k(r)}\left(\underline{tWL}_{l(r),r}\right) & \text{for } i = 1\\ \alpha_{SL,k(r),r}\,\overline{p}_{SL,k(r)}\left(\underline{tSL}_{k(r),r}\right) - \alpha_{SL,k(r),r}\,\overline{p}_{SL,k(r)}\left(\underline{tWL}_{l(r),r}\right) & \text{for } i = 2\\ \alpha_{SL,k(r),r}\,\overline{p}_{SL,k(r)}\left(\overline{tSL}_{k(r),r}\right) - \alpha_{SL,k(r),r}\,\overline{p}_{SL,k(r)}\left(\overline{tWL}_{l(r),r}\right) & \text{for } i = 3\\ \alpha_{SL,k(r),r}\,\overline{p}_{SL,k(r)}\left(\underline{tSL}_{k(r),r}\right) - \alpha_{SL,k(r),r}\,\overline{p}_{SL,k(r)}\left(\overline{tWL}_{l(r),r}\right) & \text{for } i = 4 \end{cases}$$
(7.39)

with the subscripts k(r) and l(r) defined the same as in Eq. (4.19). Specifically, k(r) identifies the SL whose failure potentially results in LOAS, and l(r) identifies the WL whose failure potentially prevents LOAS. The resultant approximations to $CDF_{PM,SL,i}(m | [t_{mn}, t_{mx}])$ for the four indicated cases are then obtained as in Eq. (4.20).

7.4 Verification Results for $CDF_{PM,SL,i}(m | [t_{mn}, t_{mx}])$. As a verification test, Fig. 13 presents a comparison of CDFs $CDF_{PM,SL,i}(m | [t_{mn}, t_{mx}])$, i = 1, 2, 3, 4, for SL property value margins for a system with two WLs and two SLs obtained by (i) quadrature-based evaluation of the integrals in Eqs. (7.19), (7.24) and (7.31) as described in Sect. 7.2 and (ii) a sampling-based calculation as described in Sect. 7.3 and performed with the CPLOAS program [64; 65] and a sample of size $n = 10^6$. The results obtained with the two evaluation procedures are essentially identical. This level of agreement provides a strong verification that the two procedures for obtaining $CDF_{PM,SL,i}(m | [t_{mn}, t_{mx}])$ are correct in both (i) mathematical development and (ii) computational implementation.

Fig. 13 Verification results for SL property value margin CDFs $CDF_{PM,SL,i}(m | [t_{mn}, t_{mx}])$, i = 1, 2, 3, 4, obtained with quadrature-based procedures (see Sect. 7.2) and sampling-based procedures (see Sect. 7.3) for (i) the four failure patterns resulting in LOAS indicated in Table 2

and (ii) the system of four links defined and illustrated in Table 1 and Fig. 1 with $[t_{mn}, t_{mx}] = [0, 200]$.

7.5 Connection Between Failure Property Margins $CDF_{PM,SL,i}(0|[t_{mn},t_{mx}]), i = 1, 2, 3, 4,$ and PLOAS. The probabilities $CDF_{PM,SL,i}(0|[t_{mn},t_{mx}]), i = 1, 2, 3, 4,$ associated with the failure property margin m = 0 defined in conjunction with Eq. (7.24) are equal to the probabilities $pF_i(t_{mx}), i = 1, 2, 3, 4$, for LOAS defined in Table 2. Establishing the indicated equalities is based on the following change in order of integration for a function f and CDFs $CDF_i, i = 1, 2,$ defined on $[t_{mn}, t_{mx}]$:

$$\int_{t_{mn}}^{t_{mx}} \left[\int_{t_{mn}}^{\tau_{1}} f(\tau_{2}) dCDF_{1}(\tau_{2}) \right] dCDF_{2}(\tau_{1}) = \int_{t_{mn}}^{t_{mx}} \left[\int_{\tau_{1}}^{t_{mx}} dCDF_{2}(\tau_{2}) \right] f(\tau_{1}) dCDF_{1}(\tau_{1}) = \int_{t_{mn}}^{t_{mx}} \left[1 - CDF_{2}(\tau) \right] f(\tau) dCDF_{1}(\tau).$$
(7.40)

With use of the preceding relationships, the representation for $CDF_{PM,SL}(0|[t_{mn},t_{mx}])$ in Eq. (7.24) becomes

$$CDF_{PM,SL,i}(0 | [t_{mn}, t_{mx}]) = \sum_{k=1}^{nSL} \int_{t_{mn}}^{t_{mx}} \left[\int_{t_{mn}}^{\tau_1} P_k(\tau_2) dCDF_{Tk}(\tau_2) \right] dCDF_{WL}(\tau_1)$$

$$= \sum_{k=1}^{nSL} \int_{t_{mn}}^{t_{mx}} \left[1 - CDF_{WL}(\tau) \right] P_k(\tau) dCDF_{Tk}(\tau)$$
(7.41)

and thus corresponds to failure patterns i = 1, 2, 3, 4 in Table 2 with

$$1 - CDF_{T,WL}(\tau) = \begin{cases} 1 - \left(1 - \prod_{l=1}^{nWL} \left[1 - CDF_{T,WL,l}(\tau)\right]\right) = \prod_{l=1}^{nWL} \left[1 - CDF_{T,WL,l}(\tau)\right] & \text{for } i = 1,2\\ 1 - \prod_{l=1}^{nWL} CDF_{T,WL,l}(\tau) & \text{for } i = 3,4 \end{cases}$$
(7.42)

and

$$P_{k}(\tau) = \begin{cases} \prod_{l=1,l\neq k}^{nSL} CDF_{T,SL,l} \text{ for } i = 1,3 \\ \prod_{l=1,l\neq k}^{nSL} \left[1 - CDF_{T,SL,l}(\tau) \right] \text{ for } i = 2,4. \end{cases}$$
(7.43)

This correspondence (i) is illustrated by the equality of $pF_i(200)$ and $CDF_{PM,SL,i}(0|[0,200])$ in Fig. 3 and Figs. 12 and 13 and (ii) provides an additional verification result that the SL property value margins in Figs. 12 and 13 have been calculated correctly.

8. Summary Discussion

The results of many complex analyses can be reduced to a single number (e.g., probability of loss of assured safety (PLOAS) in analyses of LOAS for WL/SL systems). However, it is very unwise to rely on a single number as the sole summary result of a complex analysis. Specifically, unless this number is egregiously wrong (e.g., a probability that is > 1.0 or < 0), it is often not possible to tell if this single number is a reasonable analysis result. Therefore, it is prudent to employ procedures that provide perspective on the reasonableness of summary results for complex analyses. Such procedures include (i) examination of intermediate results that underlie a final summary result, (ii) performance of verification analyses to establish that results are being calculated correctly, and (iii) performance of uncertainty and sensitivity analyses to determine both the uncertainty in analysis results and the sources of this uncertainty. The indicated procedures are discussed below in the context of the present analysis.

Examination of intermediate results. The primary motivation for the present study was to define and illustrate intermediate and summary results that can be examined to provide perspective on PLOAS results in analyses of LOAS for WL/SL systems. To this end, the following results associated with the analysis of LOAS are defined and illustrated: (i) CDFs for link failure time, link property value at link failure, link system failure time, property value at which LOAS occurs, (ii) CDFs for failure time margins defined by (time at which SL system fails) – (time at which WL system fails), (iii) CDFs for SL system property values at LOAS, (iv) CDFs for WL/SL property value margins defined by (property value at which SL system fails) – (property value at which WL system fails), and (v) CDFs for SL property value margins defined by (property value of failing SL at time of SL system failure) – (property value of this SL at time of WL system failure). Examination of these results can help provide perspectives on the nature and reasonableness of the final outcomes of an analysis of LOAS for a WL/SL system.

Performance of verification analyses. An additional motivation for the present study was to obtain verification results for the margins associated with LOAS for WL/SL systems calculated with sampling-based procedures implemented as part the CPLOAS program [64; 65]. As is the case with most sampling-based analyses, verification is difficult because the correct result is not known. Specifically, if a closed form solution was known, then there would be little reason to perform a sampling-based analysis.

Tedious checking of coding line by line and examination of intermediate results that are combined in various ways to produce the final result of interest is one way to provide "verification" for a sampling-based analysis. However, with this approach, it is not possible to be completely confident that an error in model structure or implementation has not been overlooked.

For the preceding reasons, it was decided to try to derive closed-form integral representations for the probabilities defining the CDFs for the three margin results calculated in CPLOAS: (i)

failure time margin defined by (time SL system fails) – (time WL system fails), (ii) property value margin defined by (property value at which SL system fails) – (property value at which WL system fails), and (iii) SL property value margin defined by (property value of failing SL at time of SL system failure) – (property value of this SL at time of WL system failure). In addition, integral representations were also sought for the probabilities defining the CDFs for two additional results related to margins associated with LOAS: (iv) property value at which a system of WLs or SLs fails and (v) SL property value at which LOAS occurs. After significant effort, the desired integral representations were obtained.

However, the closed-form integral representations required numerical (i.e., quadrature-based) evaluation to obtain values that could be compared with the sampling-based results produced by CPLOAS. These evaluations were obtained with use of the MATLAB numerical package [66]. In some cases, implementation of the desired integral evaluations with MATLAB turned out to be quite complex and computationally inefficient compared to sampling-based evaluations.

Fortunately, the quadrature-based calculations using MATLAB and the sampling-based calculations using CPLOAS produced CDFs for the 5 cases under consideration that matched with high precision for a test problem with 2 SLs and 2 WLs (see Figs. 5, 7, 9, 11, 13). This level of agreement provides a strong verification that the two procedures for obtaining CDFs for the five indicated results are correct in both (i) mathematical development and (ii) computational implementation.

With respect to ease of implementation, the sampling-based implementations in CPLOAS were easier to derive and implement than was the case for deriving and numerically implementing the integral-based representations. Specifically, the sampling-based procedures were developed and implemented before the possibility of developing integral-based procedures was even considered.

Another positive aspect of the verification results in this study is the independence of the development of the three components of the verification results by the three study authors: (i) Development of integral representations for margin results (performed by Jon Helton), (ii) Development and implementation of quadrature-based procedures for the evaluation of integral representations for margin results (performed by Dusty Brooks), and (iii) Development and implementation of sampling-based procedures for the calculation of margin results (performed by Cédric Sallaberry). Such independence is always desirable, but not always possible, in a verification study.

Performance of uncertainty and sensitivity analyses. Although not performed as part of the present study, uncertainty analysis and sensitivity analysis are important components of analyses for complex systems [69-76]. Uncertainty analysis provides an assessment of the uncertainty in analysis results, which is an essential part of an appropriately supported decision. Sensitivity analysis provides an assessment of the contribution of the uncertainty associated with individual analysis inputs to the uncertainty in analysis results. Specifically, sensitivity analysis provides information that supports (i) decisions on where to invest resources to reduce the uncertainty in the analysis outcomes of greatest interest (e.g., PLOAS) and (ii) verification of analysis results. Sensitivity analysis can be used as an important part of analysis verification

because an analysis error is revealed when an individual analysis input is shown to have an effect that it should not have.

The uncertainty associated with the analysis of complex systems is usually divided into aleatory uncertainty and epistemic uncertainty, with (i) aleatory uncertainty corresponding to an inherent variability in the behavior of the system under study and (ii) epistemic uncertainty corresponding to a lack of knowledge with respect to the actual value of a quantity that has a fixed value rather than a randomly varying value [16; 31; 42-45; 47-52]. Uncertainty analysis and sensitivity analysis are typically used in the investigation of the effects of epistemic uncertainty; in addition, uncertainty analysis and sensitivity analysis are also used to investigate the combined effects of aleatory uncertainty and epistemic uncertainty when both are included in an analysis (e.g., Refs. [42; 77-80]).

With respect to terminology, the descriptors aleatory uncertainty and epistemic uncertainty came into wide use in the mid 1990's. The alternative descriptors stochastic uncertainty and subjective uncertainty (e.g., as used in Refs. [43; 45; 79; 81; 82]) for aleatory uncertainty and epistemic uncertainty are no longer widely used.

The distributions for the variables α and β defined in Eqs. (2.3) and (2.4) were originally introduced into the representation of WLs and SLs to characterize random variability (i.e., aleatory uncertainty) that arises from random variability in manufactured components or possibly in environmental conditions. In an analysis in which the α 's and β 's characterize aleatory uncertainty, their distributions must be defined and most likely there will be epistemic uncertainty with respect to how these distributions should be defined (e.g., epistemic uncertainty in the definition of the three parameters in a triangular distribution used to characterize aleatory uncertainty; see Sects. 8-11 of Ref. [7] for notional examples of analyses of the type indicated in this paragraph). In a real analysis for a WL/SL system with the structure defined in this presentation, it is also likely that there will be multiple epistemically uncertainty quantities involved in the determination of the property value and failure value functions defined in Eqs. (2.1) and (2.2). Thus, an uncertainty/sensitivity analysis would be appropriate to determine the effects of the indicated epistemically uncertain quantities. In turn, an assessment of the extent to which the sensitivity analysis results are consistent with the known effects of the individual variables would constitute part of a verification analysis.

If desired, the α 's and β 's together with their associated distributions could also be used to represent epistemic uncertainty in the functions defined in Eqs. (2.1) and (2.2). However, when a probability distribution is used to represent uncertainty in an input to an analysis, it is very important to be clear on whether the distribution is intended to represent aleatory uncertainty or epistemic uncertainty. Further, when an analysis involves both aleatory uncertainty and epistemic uncertainty, it is important that the analysis be designed in a way that maintains a clear distinction between the effects of aleatory uncertainty and the effects of epistemic uncertainty (e.g., Refs. [42; 79; 80; 82-84]).

Acknowledgments

Work performed at Sandia National Laboratories (SNL), which is a multi-mission laboratory managed and operated by National Technology and Engineering Solutions of Sandia, LLC., a wholly owned subsidiary of Honeywell International, Inc., for the U.S. Department of Energy's (DOE's) National Nuclear Security Administration under Contract No. DE-NA0003525. Support and encouragement for this work was provided by Martin Pilch, Roy Hogan and Kevin Dowding. The views expressed in this article are those of the authors and do not necessarily reflect the views or policies of the DOE or SNL. The United States Government retains and the publisher, by accepting this article for publication, acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this article, or allow others to do so, for United States Government purposes.

References:

- Plummer D.W. and W.H. Greenwood. 1998. The History of Nuclear Weapon Safety Devices. In AIAA/ASME/SAE/ASEE 34th Joint Propulsion Conference and Exhibit, Cleveland, OH, July 13-15, 1998. Reston, VA: American Institute of Aeronautics and Astronautics.
- Caldwell M. and P.E. D'Antonio. 1998. A Study of Using Electronics for Nuclear Weapon Detonation Safety. In AIAA/ASME/SAE/ASEE 34th Joint Propulsion Conference and Exhibit, Cleveland, OH, July 13-15, 1998. Reston, VA: American Institute of Aeronautics and Astronautics.
- 3. Winter W.L., J.M. Covan and L.J. Dalton. 1998. Passive Safety in High-Consequence Systems. *Computer* 31:35-37.
- D'Antonio P.E. 1998. Surety Principles Development and Integration for Nuclear Weapons. In *High Consequence Operations Safety Symposium II, SAND98-1557*, ed. D Isbell, pp. 141-149. Albuquerque, NM: Sandia National Laboratories.
- Demmie P.N. 1998. A First-Principle Based Approach to Quantitative Assessment of Nuclear-Detonation Safety. In *High Consequence Operations Safety Symposium II*, *SAND98-1557*, ed. D Isbell, pp. 325-341. Albuquerque, NM: Sandia National Laboratories.
- Jones M. 1998. The Role of Microelectronics and Software in a Very High Consequence System. In *High Consequence Operations Safety Symposium II, SAND98-1557*, ed. D Isbell, pp. 411-429. Albuquerque, NM: Sandia National Laboratories.
- Helton J.C., M. Pilch and C.J. Sallaberry. 2014. Probability of Loss of Assured Safety in Systems with Multiple Time-Dependent Failure Modes: Representations with Aleatory and Epistemic Uncertainty. *Reliability Engineering and System Safety* 124:171-200.
- 8. Helton J.C., D.M. Brooks and C.J. Sallaberry. In preparation. Property Values Associated with the Failure of Individual Links in a System with Multiple Weak and Strong Links.
- 9. American Institute of Aeronautics and Astronautics. 1998. Guide for the Verification and Validation of Computational Fluid Dynamics Simulations. *Rpt. AIAA G-077-1998*, American Institute of Aeronautics and Astronautics, Reston, VA.
- 10. American Society of Mechanical Engineers. 2006. Guide for Verification and Validation in Computational Solid Mechanics. *Rpt. ASME Standard V&V 10-2006*, American Society of Mechanical Engineers, New York, NY.

- 11. Oberkampf W.L. and C.J. Roy. 2010. *Verification and Validation in Scientific Computing* New York, NY: Cambridge University Press.
- 12. Roache P.J. 2009. Fundamentals of Verification and Validation. Socorro, NM: Hermosa Publishers.
- Babuska I. and J.T. Oden. 2004. Verification and Validation in Computational Engineering and Science: Basic Concepts. *Computer Methods in Applied Mechanics and Engineering* 193:4057-4066.
- 14. Helton J.C. and M. Pilch. 2011. Guest Editorial: Quantification of Margins and Uncertainties. *Reliability Engineering and System Safety* 96:959-964.
- 15. Pilch M., T.G. Trucano and J.C. Helton. 2011. Ideas Underlying the Quantification of Margins and Uncertainties. *Reliability Engineering and System Safety* 96:965-975.
- 16. Helton J.C. 2011. Quantification of Margins and Uncertainties: Conceptual and Computational Basis. *Reliability Engineering and System Safety* 96:976-1013.
- 17. NAS/NRC (National Academy of Science/National Research Council). 2008. Evaluation of Quantification of Margins and Uncertainties for Assessing and Certifying the Reliability of the Nuclear Stockpile. Washington, DC: National Academy Press.
- Goodwin B.T. and R.J. Juzaitis. 2006. National Certification Methodology for the Nuclear Weapons Stockpile. *Rpt. UCRL-TR-223486*, Lawrence Livermore National Laboratory, Livermore, CA.
- 19. Sharp D.H. and M.M. Wood-Schultz. 2003. QMU and Nuclear Weapons Certification: What's Under the Hood? *Los Alamos Science* 28:47-53.
- Sharp D.H., T.C. Wallstrom and M.M. Wood-Schultz. 2004. Physics Package Confidence: "One" vs. "1.0". *Rpt. LA-UR-04-0496*, Los Alamos National Laboratory, Los Alamos, NM.
- 21. Booker J.N., T. Ross, M. Hamada, R. Reardon, R. Dolin, C.L. Faust and L. Najera. 2006. Engineering Index: An Engineering/Certification Metric. *Military Operations Research* 11:27-44.
- 22. Diegert K., S. Klenke, G. Novotny, R. Paulsen, M. Pilch and T. Trucano. 2007. Toward a More Rigorous Application of Margins and Uncertainties within the Nuclear Weapons Life Cycle - A Sandia Perspective. *Rpt. SAND2007-6219*, Sandia National Laboratories, Albuquerque, NM.
- 23. Higdon D.M., C.M. Anderson-Cook, J.R. Gattiker, A.P. Huzurbazar, L.M. Moore, R.R. Picard, W.H. Press, B.J. Williams, T.C. Wallstrom, L.C. Bornn and R.A. Nelson. 2008. QMU for Advanced Certification: Identifying Existing Limitations with Discussion of Solution Strategies *Rpt. LA-UR-08-06887*, Los Alamos National Laboratory, Los Alamos, NM.
- 24. Wallstrom T.C. 2008. Quantification of Margins and Uncertainty: A Bayesian Approach. *Rpt. LA-UR-08-4800*, Los Alamos National Laboratory, Los Alamos, NM.
- 25. Lorio J.F., M.A. Dvorack, M.J. Mundt, K.V. Diegert, J.T. Ringland, R. Zurn, C.M. Anderson-Cook, A. Huzurbazar, A. Wilson and Q. Fatherley. 2009. Quantifying Reliability Uncertainty: A Proof of Concept. *Rpt. SAND2009-2173*, Sandia National Laboratories, Albuquerque, NM.
- 26. Abeyta H. and et-al. 2004. Report on the Friendly Reviews of QMU at the NNSA Laboratories, Defense Programs Science Council
- 27. JASON. 2005. Quantifications of Margins and Uncertainties (QMU). *Rpt. JSR-04-3330*, The Mitre Corporation, McLean, VA.

- 28. U.S. GAO (U.S. Government Accountability Office). 2006. Nuclear Weapons: NNSA Needs to Refine and More Effectively Manage Its New Approach for Assessing and Certifying Nuclear Weapons. *Rpt. GAO-06-261*, U.S. Government Accountability Office, Washington, DC.
- 29. Iaccarino G., D. Sharp and J. Glimm. 2013. Quantification of Margins and Uncertainties Using Multiple Gates and Conditional Probabilities. *Reliability Engineering and System Safety* 114:99-113.
- 30. Ross T.J., J.M. Booker and A.C. Montoya. 2013. New Developments in Uncertainty Assessment and Uncertainty Management. *Expert Systems with Applications* 40:964-974.
- 31. Helton J.C., J.D. Johnson and C.J. Sallaberry. 2011. Quantification of Margins and Uncertainties: Example Analyses from Reactor Safety and Radioactive Waste Disposal Involving the Separation of Aleatory and Epistemic Uncertainty. *Reliability Engineering* and System Safety 96:1014-1033.
- 32. Helton J.C. and J.D. Johnson. 2011. Quantification of Margins and Uncertainties: Alternative Representations of Epistemic Uncertainty. *Reliability Engineering and System Safety* 96:1034-1052.
- 33. Wallstrom T.C. 2011. Quantification of Margins and Uncertainties: A Probabilistic Framework. *Reliability Engineering and System Safety* 96:1053-1062.
- 34. Anderson-Cook C.M., S. Crowder, A.V. Huzurbazar, J. Lorio, J. Ringland and A.G. Wilson. 2011. Quantifying Reliability Uncertainty from Catastrophic and Margin Defects: A Proof of Concept. *Reliability Engineering and System Safety* 96:1063-1075.
- 35. Wilson A.G., C.M. Anderson-Cook and A.V. Huzurbazar. 2011. A Case Study for Quantifying System Reliability and Uncertainty. *Reliability Engineering and System Safety* 96:1076-1084.
- 36. Eldred M.S., L.P. Swiler and G. Tang. 2011. Mixed Aleatory-Epistemic Uncertainty Quantification with Stochastic Expansions and Optimization-Based Interval Estimation. *Reliability Engineering and System Safety* 96:1092-1113.
- Urbina A., S. Mahadevan and T.L. Paez. 2011. Quantification of Margins and Uncertainties of Complex Systems in the Presence of Aleatoric and Epistemic Uncertainty. *Reliability Engineering and System Safety* 96:1114-1125.
- 38. Sentz K. and S. Ferson. 2011. Probabilistic Bounding Analysis in the Quantification of Margins and Uncertainties. *Reliability Engineering and System Safety* 96:1126-1136.
- 39. Iaccarino G., R. Pecnik, J. Glimm and D. Sharp. 2011. A QMU Approach for Characterizing the Operability Limits of Air-Breathing Hypersonic Vehicles. *Reliability Engineering and System Safety* 96:1150-1160.
- 40. Hemez F.M. and S. Atamturktur. 2011. The Dangers of Sparse Sampling for the Quantification of Margin and Uncertainty. *Reliability Engineering and System Safety* 96:1220-1231.
- 41. Helton J.C., D.M. Brooks and C.J. Sallaberry. 2018. Margins Associated with Loss of Assured Safety for Systems with Multiple Time-Dependent Failure Modes. *Rpt. SAND2018-1847*, Sandia National Laboratories, Albuquerque, NM.
- 42. Helton J.C. and C.J. Sallaberry. 2012. Uncertainty and Sensitivity Analysis: From Regulatory Requirements to Conceptual Structure and Computational Implementation. *IFIP Advances in Information and Communication Technology* 377 AICT:60-76.
- 43. Helton J.C. 1997. Uncertainty and Sensitivity Analysis in the Presence of Stochastic and Subjective Uncertainty. *Journal of Statistical Computation and Simulation* 57:3-76.

- 44. Helton J.C. and D.E. Burmaster. 1996. Guest Editorial: Treatment of Aleatory and Epistemic Uncertainty in Performance Assessments for Complex Systems. *Reliability Engineering and System Safety* 54:91-94.
- 45. Helton J.C. 1994. Treatment of Uncertainty in Performance Assessments for Complex Systems. *Risk Analysis* 14:483-511.
- 46. Der Kiureghian A. and O. Ditlevsen. 2009. Aleatory or Epistemic? Does It Matter? . *Structural Safety* 31:105-112.
- 47. Apostolakis G. 1999. The Distinction between Aleatory and Epistemic Uncertainties is Important: An Example from the Inclusion of Aging Effects into PSA In Proceedings of the International Topical Meeting on Probabilistic Safety Assessment, PSA '99: Risk Informed and Performance-Based Regulation in the New Millenniam 1:135-142. La Grange Park, IL: American Nuclear Society. Number of 135-142 pp.
- 48. Apostolakis G. 1990. The Concept of Probability in Safety Assessments of Technological Systems. *Science* 250:1359-1364.
- 49. Paté-Cornell M.E. 1996. Uncertainties in Risk Analysis: Six Levels of Treatment. *Reliability Engineering and System Safety* 54:95-111.
- 50. Parry G.W. 1996. The Characterization of Uncertainty in Probabilistic Risk Assessments of Complex Systems. *Reliability Engineering and System Safety* 54:119-126.
- 51. Parry G.W. and P.W. Winter. 1981. Characterization and Evaluation of Uncertainty in Probabilistic Risk Analysis. *Nuclear Safety* 22:28-42.
- 52. Hoffman F.O. and J.S. Hammonds. 1994. Propagation of Uncertainty in Risk Assessments: The Need to Distinguish Between Uncertainty Due to Lack of Knowledge and Uncertainty Due to Variability. *Risk Analysis* 14:707-712.
- 53. Hora S.C. and R.L. Iman. 1989. Expert Opinion in Risk Analysis: The NUREG-1150 Methodology. *Nuclear Science and Engineering* 102:323-331.
- 54. Thorne M.C. and M.M.R. Williams. 1992. A Review of Expert Judgement Techniques with Reference to Nuclear Safety. *Progress in Nuclear Safety* 27:83-254.
- 55. Budnitz R.J., G. Apostolakis, D.M. Boore, L.S. Cluff, K.J. Coppersmith, C.A. Cornell and P.A. Morris. 1998. Use of Technical Expert Panels: Applications to Probabilistic Seismic Hazard Analysis. *Risk Analysis* 18:463-469.
- 56. McKay M. and M. Meyer. 2000. Critique of and Limitations on the Use of Expert Judgements in Accident Consequence Uncertainty Analysis. *Radiation Protection Dosimetry* 90:325-330.
- 57. Meyer M.A. and J.M. Booker. 2001. *Eliciting and Analyzing Expert Judgment: A Practical Guide*. Philadelphia, PA: SIAM.
- 58. Ayyub B.M. 2001. Elicitation of Expert Opinions for Uncertainty and Risks, CRC Press, Boca Raton, FL.
- 59. Cooke R.M. and L.H.J. Goossens. 2004. Expert Judgement Elicitation for Risk Assessment of Critical Infrastructures. *Journal of Risk Research* 7:643-656.
- 60. Garthwaite P.H., J.B. Kadane and A. O'Hagan. 2005. Statistical Methods for Eliciting Probability Distributions. *Journal of the American Statistical Association* 100:680-700.
- 61. Helton J.C., J.D. Johnson and W.L. Oberkampf. 2007. Verification Test Problems for the Calculation of Probability of Loss of Assured Safety in Temperature Dependent Systems with Multiple Weak and Strong Links. *Reliability Engineering and System Safety* 92:1374-1387.

- 62. Helton J.C., J.D. Johnson and W.L. Oberkampf. 2009. Effect of Delayed Link Failure on Probability of Loss of Assured Safety in Temperature-Dependent Systems with Multiple Weak and Strong Links. *Reliability Engineering and System Safety* 94:294-310.
- 63. Ross S.M. 1993. Introduction to Probability Models. New York, NY: Academic Press.
- 64. Sallaberry C.J. and J.C. Helton. 2015. CPLOAS_2 User Manual. *Rpt. SAND2015-4179*, Sandia National Laboratories, Albuquerque, NM.
- 65. Groth K.M. 2014. CPLOAS_2 V2.10 Verification Report. *Rpt. SAND2014-16321*, Sandia National Laboratories, Albuquerque, NM.
- 66. MATLAB and Statistics Toolbox Release 2015b, The MathWorks, Inc, Natick, MA.
- 67. Helton J.C., W.L. Oberkampf and J.D. Johnson. 2005. Competing Failure Risk Analysis Using Evidence Theory. *Risk Analysis* 25:973-995.
- 68. Shampine L.F. 2008. MATLAB Program for Quadrature in 2D. Applied Mathematics and Computation 202:266-274.
- 69. Saltelli A., K. Chan and E.M. Scott (eds). 2000. Sensitivity Analysis. New York, NY: Wiley.
- 70. Saltelli A., M. Ratto, S. Tarantola and F. Campolongo. 2005. Sensitivity Analysis for Chemical Models. *Chemical Reviews* 105:2811-2828.
- 71. Helton J.C. and F.J. Davis. 2003. Latin Hypercube Sampling and the Propagation of Uncertainty in Analyses of Complex Systems. *Reliability Engineering and System Safety* 81:23-69.
- 72. Helton J.C., J.D. Johnson, C.J. Sallaberry and C.B. Storlie. 2006. Survey of Sampling-Based Methods for Uncertainty and Sensitivity Analysis. *Reliability Engineering and System Safety* 91:1175-1209.
- 73. Storlie C.B. and J.C. Helton. 2008. Multiple Predictor Smoothing Methods for Sensitivity Analysis: Description of Techniques. *Reliability Engineering and System Safety* 93:28-54.
- 74. Storlie C.B., L.P. Swiler, J.C. Helton and C.J. Sallaberry. 2009. Implementation and Evaluation of Nonparametric Regression Procedures for Sensitivity Analysis of Computationally Demanding Models. *Reliability Engineering and System Safety* 94:1735-1763.
- 75. Wei P., Z. Lu and S. Song. 2015. Variable Inportance Analysis: A Conprehensive Review. *Reliability Engineering and System Safety* 142:399-432.
- 76. Borgonovo E. and E. Plischke. 2016. Sensitivity Analysis: A Review of Recent Advances. *European Journal of Operational Research* 248:869-887.
- 77. Helton J.C., C.W. Hansen and C.J. Sallaberry. 2012. Uncertainty and Sensitivity Analysis in Performance Assessment for the Proposed Repository for High-Level Radioactive Waste at Yucca Mountain, Nevada. *Reliability Engineering and System Safety* 107:44-63.
- 78. Helton J.C. 1999. Uncertainty and Sensitivity Analysis in Performance Assessment for the Waste Isolation Pilot Plant. *Computer Physics Communications* 117:156-180.
- 79. Helton J.C., J.D. Johnson, A.W. Shiver and J.L. Sprung. 1995. Uncertainty and Sensitivity Analysis of Early Exposure Results with the MACCS Reactor Accident Consequence Model. *Reliability Engineering and System Safety* 48:91-127.
- 80. Helton J.C. and R.J. Breeding. 1993. Calculation of Reactor Accident Safety Goals. *Reliability Engineering and System Safety* 39:129-158.
- 81. Helton J.C., J.D. Johnson, H.-N. Jow, R.D. McCurley and L.J. Rahal. 1998. Stochastic and Subjective Uncertainty in the Assessment of Radiation Exposure at the Waste Isolation Pilot Plant. *Human and Ecological Risk Assessment* 4:469-526.

- 82. Helton J.C., D.R. Anderson, H.-N. Jow, M.G. Marietta and G. Basabilvazo. 2000. Conceptual Structure of the 1996 Performance Assessment for the Waste Isolation Pilot Plant. *Reliability Engineering and System Safety* 69:151-165.
- 83. Helton J.C., C.W. Hansen and C.J. Sallaberry. 2014. Conceptual Structure and Computational Organization of the 2008 Performance Assessment for the Proposed High-Level Radioactive Waste Repository at Yucca Mountain, Nevada. *Reliability Engineering and System Safety* 122:223-248.
- 84. Breeding R.J., J.C. Helton, E.D. Gorham and F.T. Harper. 1992. Summary Description of the Methods Used in the Probabilistic Risk Assessments for NUREG-1150. *Nuclear Engineering and Design* 135:1-27.

46



Fig. 1 Summary plots of the properties of two WLs and two SLs used in the illustration of the definition and calculation of margins for WL/SL systems with the dashed lines corresponding to the boundaries defined by $[\alpha_{mn}\overline{p}(t), \alpha_{mx}\overline{p}(t)]$ and $[\beta_{mn}\overline{q}(t), \beta_{mx}\overline{q}(t)]$: (a) WL 1, (b) WL 2, (c) SL 1, and (d) SL2.



Fig. 2 Illustration of failure properties for links defined in Table 1: (a) CDFs for link failure time (i.e., $CDF_{T,WL1}(t)$, $CDF_{T,WL2}(t)$, $CDF_{T,SL1}(t)$ and $CDF_{T,SL2}(t)$), and (b) CDFs for link property at time of link failure (i.e., $CDF_{P,WL1}(p | [t_{mn}, t_{mx}])$, $CDF_{P,WL2}(p | [t_{mn}, t_{mx}])$, $CDF_{P,SL1}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,SL2}(p | [t_{mn}, t_{mx}])$ with $[t_{mn}, t_{mx}] = [0, 200]$.







Fig. 4 Failure time margins for (i) the four failure patterns resulting in LOAS indicated in Eqs. (4.4)-(4.7) and (ii) the system of four links defined and illustrated in Table 1 and Fig. 1 with $[t_{mn}, t_{mx}] = [0, 200]$: (a) link system failure probabilities $CDF_{T,WL}(t_{WL}) = pFLF(t_{WL})$, $CDF_{T,WL}(t_{WL}) = pLLF(t_{WL})$, $CDF_{T,SL}(t_{SL}) = pFLF(t_{SL})$ and $CDF_{T,SL}(t_{SL}) = pLLF(t_{SL})$ with pLLF(t) and pFLF(t) defined in Eqs. (4.1)-(4.2), and (b) failure time margins $CDF_{TM,i}(m | [t_{mn}, t_{mx}])$ for failure pattern i, i = 1, 2, 3, 4, defined in Eq. (4.3).



Fig. 5 Verification results for failure time margins $CDF_{TM,i}(m | [t_{mn}, t_{mx}]), i = 1, 2, 3, 4$, obtained with quadrature-based procedures (see Sect. 4.2) and sampling-based procedures (see Eqs. (4.21)-(4.25) in Sect. 4.3) for (i) the four failure patterns resulting in LOAS indicated in Eqs. (4.4)-(4.7) and (ii) the system of four links defined and illustrated in Table 1 and Fig. 1 with $[t_{mn}, t_{mx}] = [0, 200]$.





Fig. 6 Property value at link system failure CDFs (i.e., $CDF_{P,WL,LLF}(p | [t_{mn}, t_{mx}])$, $CDF_{P,WL,FLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,SL,FLF}(p | [t_{mn}, t_{mx}])$ with $[t_{mn}, t_{mx}] = [0, 200]$) obtained by quadrature-based evaluation of the integrals in Eqs. (5.5) and (5.6) for systems with two WLs and systems with two SLs links defined with the WLs and SLs described and illustrated in Table 1 and Fig. 1.



Fig. 7 Verification results for property value at link system failure (i.e., $CDF_{P,WL,LLF}(p | [t_{mn}, t_{mx}])$, $CDF_{P,WL,FLF}(p | [t_{mn}, t_{mx}])$, $CDF_{P,SL,LLF}(p | [t_{mn}, t_{mx}])$ and $CDF_{P,SL,FLF}(p | [t_{mn}, t_{mx}])$ with $[t_{mn}, t_{mx}] = [0, 200]$) obtained with quadrature-based procedures (see Sect. 5.1) and sampling-based procedures (see Sect. 5.2) for systems with two WLs and systems with two SLs links defined with the WLs and SLs described and illustrated in Table 1 and Fig. 1.



Fig. 8 Property value of SL at LOAS CDFs $CDF_{P,SL,i}(p | [t_{mn}, t_{mx}])$ determined over all possible times of link failure as indicated in Table 4 for (i) failure pattern *i*, *i* = 1, 2, 3, 4, resulting in LOAS as indicated in Eqs. (4.4)-(4.7) and Table 2, (ii) the system of four links defined and illustrated in Table 1 and Fig. 1 with $[t_{mn}, t_{mx}] = [0, 200]$, and (iii) quadrature-based evaluation of the integrals in Table 4.



Fig. 9 Verification results for property value of SL at LOAS CDFs $CDF_{P,SL,i}(p | [t_{mn}, t_{mx}])$, i = 1, 2, 3, 4, obtained with quadrature-based procedures (see Sect. 5.4) and sampling-based procedures (see Sect. 5.5) for (i) the four failure patterns resulting in LOAS indicated in Eqs. (4.4)-(4.7) and (ii) the system of four links defined and illustrated in Table 1 and Fig. 1 with $[t_{mn}, t_{mx}] = [0, 200]$.



Fig. 10 Weak link (WL)/strong link (SL) property margin CDFs $CDF_{PM,i}(m | [t_{mn}, t_{mx}])$ for (i) failure pattern *i*, *i* = 1, 2, 3, 4, resulting in LOAS as indicated in Table 2, (ii) the system of four links defined and illustrated in Table 1 and Fig. 1 with $[t_{mn}, t_{mx}] = [0, 200]$, and (iii) quadrature-based evaluation of the integrals in Eq. (6.2).





Fig. 11 Verification results for WL/SL property value margin CDFs $CDF_{PM,i}(p | [t_{nn}, t_{mx}]), i = 1, 2, 3, 4$, obtained with quadrature-based procedures (see Sect. 6.1) and sampling-based procedures (see Sect. 6.2) for (i) the four failure patterns resulting in LOAS indicated in Table 2 and (ii) the system of four links defined and illustrated in Table 1 and Fig. 1 with $[t_{nn}, t_{mx}] = [0, 200]$.





Fig. 12 Strong link (SL) property margin CDFs $CDF_{PM,SL,i}(m | [t_{mn}, t_{mx}])$ for (i) failure pattern *i*, i = 1, 2, 3, 4, resulting in LOAS as indicated in Table 2, (ii) the system of four links defined and illustrated in Table 1 and Fig. 1 with $[t_{mn}, t_{mx}] = [0, 200]$, and (iii) quadrature-based evaluation of the integrals in Eqs. (7.19), (7.24) and (7.31).



Fig. 13 Verification results for SL property value margin CDFs $CDF_{PM,SL,i}(m | [t_{mn}, t_{mx}])$, i = 1, 2, 3, 4, obtained with quadrature-based procedures (see Sect. 7.2) and sampling-based procedures (see Sect. 7.3) for (i) the four failure patterns resulting in LOAS indicated in Table 2 and (ii) the system of four links defined and illustrated in Table 1 and Fig. 1 with $[t_{mn}, t_{mx}] = [0, 200]$.



Table 1 Defining properties for two WLs and two SLs used in the illustration of the definition and calculation of margins for WL/SL systems.

General Properties for Links in Fig. 1
$\overline{p}(\tau) = \frac{\overline{p}(\infty)\overline{p}(0)}{\overline{p}(0) + [\overline{p}(\infty) - \overline{p}(0)]\exp(-r_1\tau)} \text{ for all links}$
$\overline{q}(\tau)$ constant-valued for WL 1 and SL 1
$\overline{q}(\tau) = \frac{\overline{q}(0)}{1 + k\tau^{r_2}}$ for WL 2 and SL 2
Additional Properties of WL 1 in Fig. 1
$\overline{p}(\infty) = 950, \overline{p}(0) = 300, r_1 = 0.02, \overline{q}(\tau) = 650$
$d_A(\alpha)$ triangular on [0.88, 1.15] with mode 1.0
$d_B(\beta)$ triangular on [0.8, 1.15] with mode 1.0
Additional Properties of WL 2 in Fig. 1
$\overline{p}(\infty) = 850, \overline{p}(0) = 300, r_1 = 0.02$
$\overline{q}(0) = 650, k = 2.21 \times 10^{-4}, r_2 = 1.5$
$d_A(\alpha)$ triangular on [0.85, 1.2] with mode 1.0
$d_B(\beta)$ triangular on [0.75, 1.2] with mode 1.0
Additional Properties of SL 1 in Fig. 1
$\overline{p}(\infty) = 1025, \overline{p}(0) = 300, r_1 = 0.025, \overline{q}(\tau) = 775$
$d_A(\alpha)$ triangular on [0.9, 1.15] with mode 1.0
$d_B(\beta)$ uniform on [0.8, 1.15]
Additional Properties of SL 2 in Fig. 1
$\overline{p}(\infty) = 950, \overline{p}(0) = 300, r_1 = 0.025$
$\overline{q}(0) = 750, k = 1.41 \times 10^{-4}, r_2 = 1.5$
$d_A(\alpha)$ triangular on [0.8, 1.1] with mode 1.0
$d_B(\beta)$ uniform on [0.85, 1.3]

Table 2 Representation of Time-Dependent Values $pF_i(t)$, i = 1, 2, 3, 4, for PLOAS and Associated Verification Tests for Alternate Definitions of LOAS for WL/SL Systems with (i) *nWL* WLs and *nSL* SLs and (ii) independent distributions for link failure time ([62], Table 10).

Failure Pattern 1: Failure of all SLs before failure of any WL (Eqs. (2.1) and (2.5), Ref. [61])

$$pF_{1}(t) = \sum_{k=1}^{nSL} \left(\int_{t_{mn}}^{t} \left\{ \prod_{l=1,l\neq k}^{nSL} CDF_{T,SL,l}(\tau) \right\} \left\{ \prod_{j=1}^{nWL} \left[1 - CDF_{T,WL,j}(\tau) \right] \right\} dCDF_{T,SL,k}(\tau) \right)$$

Verification test: $pF_1(\infty) = nWL!nSL!/(nWL+nSL)!$

Failure Pattern 2: Failure of any SL before failure of any WL (Eqs. (3.1) and (3.4), Ref. [61])

$$pF_{2}(t) = \sum_{k=1}^{nSL} \left(\int_{t_{mn}}^{t} \left\{ \prod_{l=1, l \neq k}^{nSL} \left[1 - CDF_{T,SL,l}(\tau) \right] \right\} \left\{ \prod_{j=1}^{nWL} \left[1 - CDF_{T,WL,j}(\tau) \right] \right\} dCDF_{T,SL,k}(\tau) \right\}$$

Verification test: $pF_2(\infty) = nSL/(nWL + nSL)$

Failure Pattern 3: Failure of all SLs before failure of all WLs (Eqs. (4.1) and (4.4), Ref. [61])

$$pF_{3}\left(t\right) = \sum_{k=1}^{nSL} \left\{ \int_{t_{mn}}^{t} \left\{ \prod_{l=1, l \neq k}^{nSL} CDF_{T, SL, l}\left(\tau\right) \right\} \left\{ 1 - \prod_{j=1}^{nWL} CDF_{T, WL, j}\left(\tau\right) \right\} dCDF_{T, SL, k}\left(\tau\right) \right\}$$

Verification test: $pF_3(\infty) = nWL/(nWL + nSL)$

Failure Pattern 4: Failure of any SL before failure of all WLs (Eqs. (5.1) and (5.4), Ref. [61])

$$pF_{4}(t) = \sum_{k=1}^{nSL} \left[\int_{t_{mn}}^{t} \left\{ \prod_{l=1, l \neq k}^{nSL} \left[1 - CDF_{T,SL,l}(\tau) \right] \right\} \left\{ 1 - \prod_{j=1}^{nWL} CDF_{T,WL,j}(\tau) \right\} dCDF_{T,SL,k}(\tau)$$

Verification test: $pF_{4}(\infty) = 1 - \left[nWL!nSL! / (nWL + nSL)! \right]$

Table 3 Integration limits associated with a link in Eqs. (5.1)-(5.6) with $\overline{p}(\tau)$ increasing and $\overline{q}(\tau)$ either decreasing or constant-valued (adapted from Ref. [8], Table 7).

 $\tau_{mn}(p) = \text{ first time that link failure could occur at a property value } \tilde{p} \le p$

$$=\begin{cases} \tau_f = r^{-1}(\alpha_{mx} / \beta_{mn}) & \text{for } p_f \le p \le p_{mx} \\ \tau_f(p) = \overline{q}^{-1}(p / \beta_{mn}) & \text{for } p_{mn} \le p < p_f \text{ (not relevant for } \overline{q}(\tau) = c \text{ because } p_{mn} = p_f) \end{cases}$$

 $\tau_{mx}(p) =$ last time that link failure could occur at a property value $\tilde{p} \leq p$

$$=\begin{cases} \tau_l = r^{-1}(\alpha_{mn} / \beta_{mx}) & \text{for } p_l$$

 $\tau_{mx}(t,p) = \min\{t,\tau_{mx}(p)\}$

$$[p_{mn}(\tau), p_{mx}(\tau)] = \text{ interval of link failure values } p \text{ at time } \tau \text{ for } \alpha_{mn} / \beta_{mn} < \alpha_{mx} / \beta_{mx}$$

$$= \begin{cases} [\beta_{mn}\overline{q}(\tau), \alpha_{mx}\overline{p}(\tau)] \text{ for } \tau \in \mathcal{P}_1 = \{\tau : \tau_f = r^{-1}(\alpha_{mx} / \beta_{mn}) \le \tau \le r^{-1}(\alpha_{mx} / \beta_{mx}) = \tau_{mx}\} \\ [\beta_{mn}\overline{q}(\tau), \beta_{mx}\overline{q}(\tau)] \text{ for } \tau \in \mathcal{P}_2 = \{\tau : \tau_{mx} = r^{-1}(\alpha_{mx} / \beta_{mx}) \le \tau \le r^{-1}(\alpha_{mn} / \beta_{mn}) = \tau_{mn}\} \\ [\alpha_{mn}\overline{p}(\tau), \beta_{mx}\overline{q}(\tau)] \text{ for } \tau \in \mathcal{P}_4 = \{\tau : \tau_{mn} = r^{-1}(\alpha_{mn} / \beta_{mn}) \le \tau \le r^{-1}(\alpha_{mn} / \beta_{mx}) = \tau_l\} \end{cases}$$

$$[p_{mn}(\tau), p_{mx}(\tau)] = \text{ interval of link failure values } p \text{ at time } \tau \text{ for } \alpha_{mx} / \beta_{mx} < \alpha_{mn} / \beta_{mn}$$

$$= \begin{cases} [\beta_{mn}\overline{q}(\tau), \alpha_{mx}\overline{p}(\tau)] \text{ for } \tau \in \mathcal{P}_1 = \{\tau : \tau_f = r^{-1}(\alpha_{mx} / \beta_{mn}) \le \tau \le r^{-1}(\alpha_{mn} / \beta_{mn}) = \tau_{mn}\} \\ [\alpha_{mn}\overline{p}(\tau), \alpha_{mx}\overline{p}(\tau)] \text{ for } \tau \in \mathcal{P}_3 = \{\tau : \tau_{mn} = r^{-1}(\alpha_{mn} / \beta_{mn}) \le \tau \le r^{-1}(\alpha_{mx} / \beta_{mx}) = \tau_{mx}\} \\ [\alpha_{mn}\overline{p}(\tau), \beta_{mx}\overline{q}(\tau)] \text{ for } \tau \in \mathcal{P}_4 = \{\tau : \tau_{mx} = r^{-1}(\alpha_{mx} / \beta_{mx}) \le \tau \le r^{-1}(\alpha_{mn} / \beta_{mx}) = \tau_l\} \end{cases}$$

$$[p_{mn}(\tau), p_{mx}(\tau)] = \text{ interval of link failure values } p \text{ at time } \tau \text{ for } \alpha_{mn} / \beta_{mn} = \alpha_{mx} / \beta_{mx}$$

$$= \begin{cases} [\beta_{mn}\overline{q}(\tau), \alpha_{mx}\overline{p}(\tau)] \text{ for } \tau \in \mathcal{P}_{1} = \{\tau : \tau_{f} = r^{-1}(\alpha_{mx} / \beta_{mn}) \leq \tau \leq r^{-1}(\alpha_{mx} / \beta_{mx}) = \tau_{mx} \} \\ [\alpha_{mn}\overline{p}(\tau), \beta_{mx}\overline{q}(\tau)] \text{ for } \tau \in \mathcal{P}_{4} = \{\tau : \tau_{mx} = r^{-1}(\alpha_{mx} / \beta_{mx}) \leq \tau \leq r^{-1}(\alpha_{mn} / \beta_{mx}) = \tau_{l} \} \end{cases}$$

$$p_{mx}(p, \tau) = \min\{p, p_{mx}(\tau)\}$$

Table 4 Representation of $CDF_{P,SL,i}(p | [t_{mn}, t_{mx}])$, i = 1, 2, 3, 4, for (i) SL system property at time of LOAS, (ii) *nWL* WLs and *nSL* SLs, (iii) independent distributions for link failure time, and (iv) the integral over $[t_{mn}, t_{mx}]$ equal to 0 for SL k and $t_{mx} \le \tau_{mn,k}(p)$ with $\tau_{mn,k}(p)$ and other integration limits defined in Table 3.

$$\begin{aligned} \text{Failure Pattern 1: Failure of all SLs before failure of any WL} \\ CDF_{P,SL,1}(p \mid [t_{mn}, t_{mx}]) &= \sum_{k=1}^{nSL} \left(\int_{t_{mn}}^{t_{mx}} \left\{ \prod_{l=1, l \neq k}^{nSL} CDF_{T,SL,l}(\tau) \right\} \left\{ \prod_{j=1}^{nWL} \left[1 - CDF_{T,WL,j}(\tau) \right] \right\} CDF_{P,SL,k}(p \mid \tau) dCDF_{T,SL,k}(\tau) \right) \\ &= \sum_{k=1}^{nSL} \left(\int_{\tau_{mn,k}(p)}^{\tau_{mx,k}(t_{mx},p)} \left\{ \prod_{l=1, l \neq k}^{nSL} CDF_{T,SL,l}(\tau) \right\} \left\{ \prod_{j=1}^{nWL} \left[1 - CDF_{T,WL,j}(\tau) \right] \right\} \left[d \left[\frac{1}{r_k(\tau)} \right] / d\tau \right\} \\ &\qquad \times \left\{ \int_{p_{mn,k}(\tau)}^{p_{mx,k}(p,\tau)} \left\{ \frac{\tilde{p}}{\bar{p}_k^2(\tau)} \right\} d_{Ak} \left[\tilde{p} / \bar{p}_k(\tau) \right] d_{Bk} \left[\tilde{p} / \bar{q}_k(\tau) \right] d\tilde{p} \right\} d\tau \end{aligned}$$

Failure Pattern 2: Failure of any SL before failure of any WL

$$CDF_{P,SL,2}\left(p \mid [t_{mn}, t_{mx}]\right) = \sum_{k=1}^{nSL} \left(\int_{t_{mn}}^{t_{mx}} \left\{ \prod_{l=1,l \neq k}^{nSL} \left[1 - CDF_{T,SL,l}\left(\tau\right) \right] \right\} \left\{ \prod_{j=1}^{nWL} \left[1 - CDF_{T,WL,j}\left(\tau\right) \right] \right\} CDF_{P,SL,k}\left(p \mid \tau\right) dCDF_{T,SL,k}\left(\tau\right) \right)$$

$$= \sum_{k=1}^{nSL} \left(\int_{\tau_{mn,k}(p)}^{\tau_{mx,k}(t_{mx},p)} \left\{ \prod_{l=1,l \neq k}^{nSL} \left[1 - CDF_{T,SL,l}\left(\tau\right) \right] \right\} \left\{ \prod_{j=1}^{nWL} \left[1 - CDF_{T,WL,j}\left(\tau\right) \right] \right\} \left\{ d\left[\frac{1}{r_{k}(\tau)} \right] / d\tau \right\}$$

$$\times \left\{ \int_{p_{mn,k}(\tilde{\tau})}^{p_{mx,k}(p,\tau)} \left\{ \frac{\tilde{p}}{\bar{p}_{k}^{2}(\tau)} \right\} d_{Ak}\left[\tilde{p} / \bar{p}_{k}(\tau) \right] d_{Bk}\left[\tilde{p} / \bar{q}_{k}(\tau) \right] d\tilde{p} \right\} d\tau \right\}$$

Failure Pattern 3: Failure of all SLs before failure of all WLs

$$CDF_{P,SL,3}(p \mid [t_{mn}, t_{mx}]) = \sum_{k=1}^{nSL} \left\{ \int_{t_{mn}}^{t_{mx}} \left\{ \prod_{l=1, l \neq k}^{nSL} CDF_{T,SL,l}(\tau) \right\} \left\{ 1 - \prod_{j=1}^{nWL} CDF_{T,WL,j}(\tau) \right\} CDF_{P,SL,k}(p \mid \tau) dCDF_{T,SL,k}(\tau) \right\}$$
$$= \sum_{k=1}^{nSL} \left\{ \int_{\tau_{mn,k}(p)}^{\tau_{mx,k}(t_{mx},p)} \left\{ \prod_{l=1, l \neq k}^{nSL} CDF_{T,SL,l}(\tau) \right\} \left\{ 1 - \prod_{j=1}^{nWL} CDF_{T,WL,j}(\tau) \right\} \left\{ d\left[\frac{1}{r_k(\tau)} \right] / d\tau \right\}$$
$$\times \left\{ \int_{p_{mn,k}(\tau)}^{p_{mx,k}(p,\tau)} \left\{ \frac{\tilde{p}}{\bar{p}_k^2(\tau)} \right\} d_{Ak} \left[\tilde{p} / \bar{p}_k(\tau) \right] d_{Bk} \left[\tilde{p} / \bar{q}_k(\tau) \right] d\tilde{p} \right\} d\tau \right\}$$

Failure Pattern 4: Failure of any SL before failure of all WLs

$$CDF_{P,SL,4}\left(p \mid [t_{mn}, t_{mx}]\right) = \sum_{k=1}^{nSL} \left(\int_{t_{mn}}^{t_{mx}} \left\{ \prod_{l=1, l \neq k}^{nSL} \left[1 - CDF_{T,SL,l}\left(\tau\right) \right] \right\} \left\{ 1 - \prod_{j=1}^{nWL} CDF_{T,WL,j}\left(\tau\right) \right\} CDF_{P,SL,k}\left(p \mid \tau\right) dCDF_{T,SL,k}\left(\tau\right) \right\} dCDF_{T,SL,k}\left(\tau\right) dCD$$

Table 5 Intervals $[\alpha_{mn}(\tau), \alpha_{mx}(\tau)]$ of values for α resulting in link failure conditional on link failure at time τ with $\overline{p}(\tau)$ increasing and $\overline{q}(\tau)$ either decreasing or constant-valued (adapted from Ref. [8], Tables 4 and 5).

 $[\alpha_{mn}(\tau), \alpha_{mx}(\tau)] = \text{ interval of } \alpha \text{ values resulting in link failure conditional on link failure at time } \tau$ for $\alpha_{mn} / \beta_{mn} < \alpha_{mx} / \beta_{mx}$ $= \begin{cases} [\beta_{mn}r(\tau), \alpha_{mx}] \text{ for } \tau \in \mathcal{P}_1 = \{\tau : \tau_f = r^{-1}(\alpha_{mx} / \beta_{mn}) \le \tau \le r^{-1}(\alpha_{mx} / \beta_{mx}) = \tau_{mx} \} \\ [\beta_{mn}r(\tau), \beta_{mx}r(\tau)] \text{ for } \tau \in \mathcal{P}_2 = \{\tau : \tau_{mx} = r^{-1}(\alpha_{mx} / \beta_{mx}) \le \tau \le r^{-1}(\alpha_{mn} / \beta_{mn}) = \tau_{mn} \} \\ [\alpha_{mn}, \beta_{mx}r(\tau)] \text{ for } \tau \in \mathcal{P}_4 = \{\tau : \tau_{mn} = r^{-1}(\alpha_{mn} / \beta_{mn}) \le \tau \le r^{-1}(\alpha_{mn} / \beta_{mx}) = \tau_l \} \end{cases}$

 $[\alpha_{mn}(\tau), \alpha_{mx}(\tau)] = \text{ interval of } \alpha \text{ values resulting in link failure conditional on link failure at time } \tau \text{ for } \alpha_{mx} / \beta_{mx} < \alpha_{mn} / \beta_{mn}$ $= \begin{cases} [\beta_{mn}r(\tau), \alpha_{mx}] \text{ for } \tau \in \mathcal{P}_1 = \{\tau : \tau_f = r^{-1}(\alpha_{mx} / \beta_{mn}) \leq \tau \leq r^{-1}(\alpha_{mn} / \beta_{mn}) = \tau_{mn} \} \\ [\alpha_{mn}, \alpha_{mx}] \text{ for } \tau \in \mathcal{P}_3 = \{\tau : \tau_{mn} = r^{-1}(\alpha_{mn} / \beta_{mn}) \leq \tau \leq r^{-1}(\alpha_{mx} / \beta_{mx}) = \tau_{mx} \} \\ [\alpha_{mn}, \beta_{mx}r(\tau)] \text{ for } \tau \in \mathcal{P}_4 = \{\tau : \tau_{mx} = r^{-1}(\alpha_{mx} / \beta_{mx}) \leq \tau \leq r^{-1}(\alpha_{mn} / \beta_{mx}) = \tau_l \} \end{cases}$ $[\alpha_{mn}(\tau), \alpha_{mx}(\tau)] = \text{ interval of } \alpha \text{ values resulting in link failure conditional on link failure at time } \tau \text{ for } \alpha = /\beta_{mx} - \beta_{mx} / \beta_{mx} = \alpha_{mx} / \beta_{mx} \end{cases}$

 $\int \operatorname{for} \alpha_{mn} / \beta_{mn} = \alpha_{mx} / \beta_{mx}$ $= \begin{cases} [\beta_{mn}r(\tau), \alpha_{mx}] \text{ for } \tau \in \mathcal{P}_1 = \{\tau : \tau_f = r^{-1}(\alpha_{mx} / \beta_{mn}) \le \tau \le r^{-1}(\alpha_{mx} / \beta_{mx}) = \tau_{mx} \} \\ [\alpha_{mn}, \beta_{mx}r(\tau)] \text{ for } \tau \in \mathcal{P}_4 = \{\tau : \tau_{mx} = r^{-1}(\alpha_{mx} / \beta_{mx}) \le \tau \le r^{-1}(\alpha_{mn} / \beta_{mx}) = \tau_l \} \end{cases}$